

CORPORATION OF THE TOWN OF PRESCOTT

BY-LAW #07-2014

BEING A BY-LAW TO ADOPT AN ASSET MANAGEMENT PLAN FOR THE CORPORATION OF THE TOWN OF PRESCOTT.

WHEREAS Section 11(2) of the *Municipal Act, 2001*, as amended, authorizes the Municipality to pass By-laws respecting the financial management of the municipality and its local boards;

AND WHEREAS the Council of the Corporation of the Town of Prescott deems it expedient to adopt an Asset Management Plan; attached hereto as Schedule A; to address the challenges of current and emerging municipal infrastructure needs; and allow needs to be prioritized over wants; and will guide the municipality in making the best possible decisions regarding the building, operating, maintaining, renewing, replacing and disposing of infrastructure assets; with the objective being to maximize benefits, manage risk, and provide satisfactory levels of service to the public in a sustainable manner; while setting strategic priorities to optimize decision-making about when and how to proceed with investments;

AND WHEREAS in 2010 Council adopted a Tangible Capital Assets (TCA) Policy and completed an inventory of all TCA; and on December 16, 2013 Council received the Asset Management Plan for the Town of Prescott prepared by Public Sector Digest which identified opportunities for Council to consider;

NOW THEREFORE the Council of The Corporation of the Town of Prescott does hereby adopt the "Asset Management Plan" attached hereto as Schedule "A" which includes an Executive Summary; Introduction; State of the Infrastructure; Infrastructure Report Card; Desired Levels of Service; Asset Management Strategy; and a Financial Strategy;

AND THAT the Council of the Corporation of the Town of Prescott shall discuss the Asset Management Plan annually during the Budget process, to determine if amendments are required to the infrastructure priorities;

AND THAT the Council of the Corporation of the Town of Prescott shall also review the entire Asset Management Plan at least each Council term;

AND THAT this By-Law shall come into force and take effect on the date of its passing.

READ A FIRST AND SECOND TIME, THIS 3rd DAY OF March, 2014.



Mayor



Clerk

READ A THIRD TIME AND FINALLY PASSED THIS 3rd DAY OF March, 2014.




Mayor



Clerk

Adopted By-Law #07-2014

March 3, 2014



THE ASSET MANAGEMENT PLAN FOR THE TOWN OF PRESCOTT

2013




SUBMITTED DECEMBER 2013
BY PUBLIC SECTOR DIGEST
148 FULLARTON STREET, SUITE 1410
LONDON, ONTARIO, N6A 5P3

State of the Infrastructure

The Town of Prescott

AVERAGE ANNUAL FUNDING REQUIRED vs. AVERAGE ANNUAL FUNDING AVAILABLE



Total Annual Deficit: \$1,367,000

 Annual Funding Available
 Annual Funding Deficit

PUBLIC SECTOR DIGEST

INTELLIGENCE FOR THE PUBLIC SECTOR.

148 Fullarton Street, Suite 1410
London, Ontario, Canada
N6A 5P3
T: 519.690.2565 F: 519.649.2010
www.publicsectordigest.com
www.citywidesolutions.com

December 2013

The Town of Prescott
P.O. Box 160, 360 Dibble Street West
Prescott, Ontario, K0E 1T0

Attention: Laurie Kirkby, Treasurer

We are pleased to submit the 2013 Asset Management Plan (AMP) for the Town of Prescott. This AMP complies with the requirements as outlined within the provincial *Building Together Guide for Municipal Asset Management Plans*. It will serve as a strategic, tactical, and financial document, ensuring the management of the municipal infrastructure follows sound asset management practices and principles, while optimizing available resources and establishing desired levels of service. Given the broad and profound impact of asset management on the community, and the financial & administrative complexity involved in this ongoing process, we recommend that senior decision-makers from across the organization are actively involved in its implementation.

The performance of a community's infrastructure provides the foundation for its economic development, competitiveness, prosperity, reputation, and the overall quality of life for its residents. As such, we are appreciative of your decision to entrust us with the strategic direction of its infrastructure and asset management planning, and are confident that this AMP will serve as a valuable tool.

Sincerely,
The Public Sector Digest Inc.



Matthew Dawe
Vice President
mdawe@publicsectordigest.com



Israr Ahmad
Managing Editor
iahmad@publicsectordigest.com

PUBLIC SECTOR DIGEST

INTELLIGENCE FOR THE PUBLIC SECTOR.

Contacts

Matthew Dawe
Vice President
mdawe@publicsectordigest.com

Israr Ahmad
Managing Editor
iahmad@publicsectordigest.com

Christine Beneteau
Data Analyst
cbeneteau@publicsectordigest.com

Chad Gale
Data Analyst
cgale@publicsectordigest.com

Jona Mema
Data Analyst
jmema@publicsectordigest.com

Salman Zafar
Data Analyst
szafar@publicsectordigest.com

Tyler Sutton
Senior Research Analyst
tsutton@publicsectordigest.com

Matthew Van Dommelen
Regional Director
mvandommelen@publicsectordigest.com

Gabe Metron
Regional Director
gmetron@publicsectordigest.com

Holly Jennings
Account Manager
hjennings@publicsectordigest.com

LEGAL NOTICE

This report has been prepared by The Public Sector Digest Inc. ("PSD") in accordance with instructions received from the Town of Prescott (the "Client") and for the sole use of the Client. The content of (and recommendations) this report reflects the best judgement of PSD personnel based on the information made available to PSD by the Client. Unauthorized use of this report for any other purpose, or by any third party, without the express written consent of PSD, shall be at such third party's sole risk without liability to PSD.

This report is protected by copyright.

Table of Contents

1.0 Executive Summary	4
2.0 Introduction	7
2.1 Importance of Infrastructure.....	7
2.2 Asset Management Plan (AMP) - Relationship to Strategic Plan	8
2.3 AMP - Relationship to other Plans	8
2.4 Purpose and Methodology.....	9
2.5 CityWide Software alignment with AMP.....	11
3.0 State of the Infrastructure (SOTI)	12
3.1 Objective and Scope	12
3.2 Approach	12
3.2.1 Base Data.....	12
3.2.2 Asset Deterioration Review.....	12
3.2.3 Identify Sustainable Investment Requirements	13
3.2.4 Asset Rating Criteria.....	13
3.2.5 Infrastructure Report Card.....	13
3.2.6 General Methodology and Reporting Approach.....	14
3.3 Road Network	15
3.3.1 What do we own?	16
3.3.2 What is it worth?	16
3.3.3 What condition is it in?	17
3.3.4 What do we need to do to it?	17
3.3.5 When do we need to do it?	17
3.3.6 How much money do we need?	18
3.3.7 How do we reach sustainability?.....	18
3.3.8 Recommendations	19
3.5 Bridges & Culverts.....	20
3.5.1 What do we own?	21
3.5.2 What is it worth?	21
3.5.3 What condition is it in?	21
3.5.4 What do we need to do to it?	22
3.5.5 When do we need to do it?	22
3.5.6 How much money do we need?	23
3.5.7 How do we reach sustainability?.....	23
3.5.8 Recommendations	23
3.6 Water Network	24
3.6.1 What do we own?	25
3.6.2 What is it worth?	25
3.6.3 What condition is it in?	26

3.6.4 What do we need to do to it?	27
3.6.5 When do we need to do it?	27
3.6.6 How much money do we need?	29
3.6.7 How do we reach sustainability?	29
3.6.8 Recommendations	30
3.7 Sanitary Sewer Network.....	31
3.7.1 What do we own?	32
3.7.2 What is it worth?	32
3.7.3 What condition is it in?	34
3.7.4 What do we need to do to it?	34
3.7.5 When do we need to do it?	35
3.7.6 How much money do we need?	36
3.7.7 How do we reach sustainability?	36
3.7.8 Recommendations	37
3.8 Storm Sewer Network.....	38
3.8.1 What do we own?	39
3.8.2 What is it worth?	39
3.8.3 What condition is it in?	41
3.8.4 What do we need to do to it?	42
3.8.5 When do we need to do it?	42
3.8.6 How much money do we need?	43
3.8.7 How do we reach sustainability?	43
3.8.8 Recommendations	44
4.0 Infrastructure Report Card.....	45
5.0 Desired Levels of Service	46
5.1 Key factors that influence a level of service:.....	46
5.1.1 Strategic and Corporate Goals	46
5.1.2 Legislative Requirements	46
5.1.3 Expected Asset Performance.....	46
5.1.4 Community Expectations.....	46
5.1.5 Availability of Finances.....	47
5.2 Key Performance Indicators	47
5.3 Transportation Services	48
5.3.1 Service Description	48
5.3.2 Scope of Services.....	49
5.3.3 Performance Indicators (reported annually)	49
5.4 Water / Sanitary / Storm Networks	49
5.4.1 Service Description	49
5.4.2 Scope of services	51
5.4.3 Performance Indicators (reported annually)	51
6.0 Asset Management Strategy	52
6.1 Objective	52
6.2 Non-Infrastructure Solutions and Requirements	52
6.3 Condition Assessment Programs	52
6.3.1 Pavement Network Inspections	53
6.3.2 Bridges & Culverts (greater than 3m) Inspections	54

6.3.3 Sewer Network Inspections (Sanitary & Storm)	54
6.3.4 Water network inspections	55
6.4 AM Strategy – Life Cycle Analysis Framework	57
6.4.1 Paved Roads	57
6.4.2 Gravel Roads	59
6.4.3 Sanitary and Storm Sewers.....	59
6.4.4 Bridges & Culverts (greater than 3m span)	61
6.4.5 Water Network.....	61
6.5 Growth and Demand	64
6.6 Project Prioritization	64
6.6.1 Risk Matrix and Scoring Methodology.....	64
7.0 Financial Strategy	67
7.1 General overview of financial plan requirements	67
7.2 Financial information relating to Prescott's AMP	68
7.2.1 Funding objective	68
7.3 Tax funded assets	68
7.3.1 Current funding position.....	68
7.3.2 Recommendations for full funding.....	69
7.4 Rate funded assets.....	70
7.4.1 Current funding position.....	70
7.4.2 Recommendations for full funding.....	70
7.5 Use of debt	72
7.6 Use of reserves	74
7.6.1 Available reserves	74
7.6.2 Recommendation.....	75
8.0 Appendix A: Report Card Calculations	76


1.0 Executive Summary

The performance of a community's infrastructure provides the foundation for its economic development, competitiveness, prosperity, reputation, and the overall quality of life for its residents. Reliable and well-maintained infrastructure assets are essential for the delivery of critical core services for the citizens of a municipality.

A technically precise and financially rigorous asset management plan, diligently implemented, will mean that sufficient investments are made to ensure delivery of sustainable infrastructure services to current and future residents. The plan will also indicate the respective financial obligations required to maintain this delivery at established levels of service.

This Asset Management Plan (AMP) for the Town of Prescott meets all requirements as outlined within the provincial *Building Together Guide for Municipal Asset Management Plans*. It will serve as a strategic, tactical, and financial document, ensuring the management of the municipal infrastructure follows sound asset management practices and principles, while optimizing available resources and establishing desired levels of service. Given the expansive financial and social impact of asset management on both a municipality, and its citizens, it is critical that senior decision-makers, including department heads as well as the chief executives, are strategically involved.


Measured in 2012 dollars, the replacement value of the asset classes analyzed totaled **\$111 million** for Prescott.



While the municipality is responsible for the strategic direction, it is the taxpayer in Prescott who ultimately bears the financial burden. As such, a 'cost per household' (CPH) analysis was conducted for each of the asset classes to determine the financial obligation of each household in sharing the replacement cost of the municipality's assets. Such a measurement can serve as an excellent communication tool for both the administration and the council in communicating the importance of asset management to the citizen. The diagram below illustrates the total CPH, as well as the CPH for individual asset classes.

Infrastructure Replacement Cost Per Household

Total: \$51,607 per household



In assessing the municipality's state of the infrastructure, we examined, and graded, both the current condition (Condition vs. Performance) of the asset classes as well as the municipality's financial capacity to fund the asset's average annual requirement for sustainability (Funding vs. Need). We then generated the municipality's infrastructure report card. Prescott received a **cumulative GPA of 'D'**, with an **annual infrastructure deficit of \$1.37 million**. For three of the asset classes, including bridges & culverts, sanitary network, and storm network, a grade of 'F' was assigned on the Funding vs. Need dimension. For the remaining classes of roads and water infrastructure, a grade of 'D' was assigned.

Prescott's grades on the Condition vs. Performance dimension were better, but equally consistent. The town received a 'B' in both the road network and its bridges & culverts assets. This grade suggests that only minor deterioration is evident in asset conditions. For water infrastructure, a grade of 'C' was assigned, and the town received a 'C+' for both its sanitary and storm sewer networks. A grade of 'C' suggests increasingly visible signs of deterioration and a possible compromise in asset function. Further, while the road network is generally in good condition, some assets are nearing the end of their useful life. These replacement needs will total approximately \$4 million in the next five years. Similarly, the replacement needs for the water and sanitary network total approximately \$11 million as a portion of both infrastructure assets are in critical condition based on age data.

In order for an AMP to be effectively put into action, it must be integrated with financial planning and long-term budgeting. We have developed scenarios that would enable Prescott to achieve full funding within 5 years or 10 years for the following: tax funded assets, including road network (paved roads), bridges & culverts, storm sewer network, and; rate funded assets, including water network, and sanitary sewer network.

The average annual investment requirement for paved roads, bridges & culverts, and storm sewers is \$1,027,000. Annual revenue currently allocated to these assets for capital purposes is \$410,000 leaving an annual deficit of \$617,000. To put it another way, these infrastructure categories are currently funded at 40% of their long-term requirements. In 2013, Prescott has annual tax revenues of \$5,023,000. Without consideration of any other sources of revenue, full funding would require a tax increase of 12.3% over time. We recommend a 10 year option which involves full funding being achieved over 10 years by:

- a) over the phase-in period, reallocating the \$20,000 of gas tax revenue currently being allocated to rate funded asset categories (as listed in section 7.4 of this report) to the tax funded asset categories as outlined above.
- b) when realized, reallocating the debt cost reductions of \$32,000 to the infrastructure deficit as outlined above.
- c) increasing tax revenues by 1.1% each year for the next 10 years solely for the purpose of phasing in full funding to the tax funded asset categories.
- d) allocating the \$196,000 of gas tax revenue to the tax funded asset categories.
- e) increasing existing and future infrastructure budgets by the applicable inflation index on an annual basis in addition to the deficit phase-in.

The average annual investment requirement for sanitary services and water services is \$1,137,000. Annual revenue currently allocated to these assets for capital purposes is \$387,000 leaving an annual deficit of \$750,000. To put it another way, these infrastructure categories are currently funded at 34% of their long-term requirements. In 2013, Prescott has annual sanitary revenues of \$1,482,000 and annual water revenues of \$1,245,000. Without consideration of any other sources of revenue, full funding would require the following increases over time: an increase of 38.5% for sanitary services, and an increase of 14.5% for water services. We recommend a 10 year option which involves full funding being achieved over 10 years by:

- a) over the phase-in period, reallocating the gas tax revenue of \$20,000 currently being allocated to sanitary services to the tax funded asset categories in section 7.3 of this report.
- b) when realized, reallocating the debt cost reductions of \$472,000 for sanitary services and \$23,000 for water services to the applicable infrastructure deficit.
- c) increasing rate revenues by 0.8% for sanitary services and 1.3% for water services each year for the next 10 years solely for the purpose of phasing in full funding to the rate based asset categories covered in this AMP.

The revenue options outlined in this plan allow Prescott to fully fund its long-term infrastructure requirements without further use of debt. However, as explained in sections 7.3.2 and 7.4.2, the recommended condition rating analysis may require otherwise. Prescott's reserves totaling approximately \$3.8 million are available for use by applicable asset categories during the phase-in period to full funding. This, coupled with Prescott's judicious use of debt in the past, allows the scenarios to assume that, if required, available reserves and debt capacity can be used for high priority and emergency infrastructure investments in the short to medium-term.

2.0 Introduction

This Asset Management Plan meets all provincial requirements as outlined within the Ontario Building Together Guide for Municipal Asset Management Plans. As such, the following key sections and content are included:

1. Executive Summary and Introduction
2. State of the Current Infrastructure
3. Desired Levels of Service
4. Asset Management Strategy
5. Financial Strategy

The following asset classes are addressed:

1. **Road Network:** Urban and rural paved
2. **Bridges & Culverts:** Bridges with a span greater than 3m
3. **Water Network:** Water mains, hydrants, valves, facilities
4. **Sanitary Sewer Network:** Sanitary sewer mains, manholes, facilities
5. **Storm Sewer Network:** Storm sewer mains, catch basins, manholes

Municipalities are encouraged to cover all asset classes in future iterations of the AMP.

This asset management plan will serve as a strategic, tactical, and financial document ensuring the management of the municipal infrastructure follows sound asset management practices and principles, while optimizing available resources and establishing desired levels of service.

At a strategic level, within the State of the Current Infrastructure section, it will identify current and future challenges that should be addressed in order to maintain sustainable infrastructure services on a long-term, life cycle basis.

It will outline a Desired Level of Service (LOS) Framework for each asset category to assist the development and tracking of LOS through performance measures across strategic, financial, tactical, operational, and maintenance activities within the organization.

At a tactical level, within the Asset Management Strategy section, it will develop an implementation process to be applied to the needs-identification and prioritization of renewal, rehabilitation, and maintenance activities, resulting in a 10 year plan that will include growth projections.

At a financial level, within the Financial Strategy section, a strategy will be developed that fully integrates with other sections of this asset management plan, to ensure delivery and optimization of the 10 year infrastructure budget.

Through the development of this plan, all data, analysis, life cycle projections, and budget models will be provided through the Public Sector Digest's CityWide suite of software products. The software and plan will be synchronized, will evolve together, and therefore, will allow for ease of updates, and annual reporting of performance measures and overall results.

This will allow for continuous improvement of the plan and its projections. It is therefore recommended that the plan be revisited and updated on an annual basis, particularly as more detailed information becomes available.

2.1 Importance of Infrastructure

Municipalities throughout Ontario, large and small, own a diverse portfolio of infrastructure assets that in turn provide a varied number of services to their citizens. The infrastructure, in essence, is a conduit for the various public services the municipality provides, e.g., the roads supply a transportation network service; the water infrastructure supplies a clean drinking water service. A community's prosperity, economic

development, competitiveness, image, and overall quality of life are inherently and explicitly tied to the performance of its infrastructure.

2.2 Asset Management Plan (AMP) - Relationship to Strategic Plan

The major benefit of strategic planning is the promotion of strategic thought and action. A strategic plan spells out where an organization wants to go, how it's going to get there, and helps decide how and where to allocate resources, ensuring alignment to the strategic priorities and objectives. It will help identify priorities and guide how municipal tax dollars and revenues are spent into the future.

The strategic plan usually includes a vision and mission statement, and key organizational priorities with alignment to objectives and action plans. Given the growing economic and political significance of infrastructure, the asset management plan will become a central component of most municipal strategic plans, influencing corporate priorities, objectives, and actions.


2.3 AMP - Relationship to other Plans

An asset management plan is a key component of the municipality's planning process linking with multiple other corporate plans and documents. For example:

- **The Official Plan** – The AMP should utilize and influence the land use policy directions for long-term growth and development as provided through the Official Plan.
- **Long Term Financial Plan** – The AMP should both utilize and conversely influence the financial forecasts within the long-term financial plan.
- **Capital Budget** – The decision framework and infrastructure needs identified in the AMP form the basis on which future capital budgets are prepared.
- **Infrastructure Master Plans & Growth Management Plan.** The AMP will utilize goals and will influence projections from infrastructure master plans and growth management plan.
- **By-Laws, standards, and policies** – The AMP will influence and utilize policies and by-laws related to infrastructure management practices and standards.
- **Regulations** – The AMP must recognize and abide by industry and senior government regulations.
- **Business Plans** – The service levels, policies, processes, and budgets defined in the AMP are incorporated into business plans as activity budgets, management strategies, and performance measures.

2.4 Purpose and Methodology

The following diagram depicts the approach and methodology, including the key components and links between those components that embody this asset management plan:



It can be seen from the above that a municipality's infrastructure planning starts at the corporate level with ties to the strategic plan, alignment to the community's expectations, and compliance with industry and government regulations.

Then, through the State of the Infrastructure analysis, overall asset inventory, valuation, condition and performance are reported. Also, a life cycle analysis of needs for each infrastructure class is conducted. This analysis yields the sustainable funding level, compared against actual current funding levels, and determines whether there is a funding surplus or deficit for each infrastructure program. The overall measure of condition and available funding is finally scored for each asset class and presented as a star rating (similar to the hotel star rating) and a letter grade (A-F) within the Infrastructure Report card.

From the lifecycle analysis above, the municipality gains an understanding of the level of service provided today for each infrastructure class and the projected level of service for the future. The next section of the AMP provides a framework for a municipality to develop a Desired Level of Service (or target service level) and develop performance measures to track the year-to-year progress towards this established target level of service.

The Asset Management Strategy then provides a detailed analysis for each infrastructure class. Included in this analysis are best practices and methodologies from within the industry which can guide the overall management of the infrastructure in order to achieve the desired level of service. This section also provides an overview of condition assessment techniques for each asset class; life cycle interventions required, including those interventions that yield the best return on investment; and prioritization techniques, including risk quantification, to determine which priority projects should move forward into the budget first.

The Financing Strategy then fully integrates with the asset management strategy and asset management plan, and provides a financial analysis that optimizes the 10 year infrastructure budget. All revenue sources available are reviewed, such as the tax levy, debt allocations, rates, reserves, grants, gas tax, development charges, etc., and necessary budget allocations are analysed to inform and deliver the infrastructure programs.


Finally, in subsequent updates to this AMP, actual project implementation will be reviewed and measured through the established performance metrics to quantify whether the desired level of service is achieved or achievable for each infrastructure class. If shortfalls in performance are observed, these will be discussed and alternate financial models or service level target adjustments will be presented.

2.5 CityWide Software alignment with AMP

The plan will be built and developed hand in hand with a database of municipal infrastructure information in the CityWide software suite of products. The software will ultimately contain the municipality's asset base, valuation information, life cycle activity predictions, costs for activities, sustainability analysis, project prioritization parameters, key performance indicators and targets, 10 year asset management strategy, and the financial plan to deliver the required infrastructure budget.

The software and plan will be synchronized, and will evolve together year-to-year as more detailed information becomes available. This synchronization will allow for ease of updates, modeling and scenario building, and annual reporting of performance measures and results. This will allow for continuous improvement of the plan and its projections. It is therefore recommended that it is revisited and updated on an annual basis.

The following diagram outlines the various CityWide software products and how they align to the various components of the AMP.



3.0 State of the Infrastructure (SOTI)

3.1 Objective and Scope

Objective: To identify the state of the municipality's infrastructure today and the projected state in the future if current funding levels and management practices remain status quo.

The analysis and subsequent communication tools will outline future asset requirements, will start the development of tactical implementation plans, and ultimately assist the organization to provide cost effective sustainable services to the current and future community.

The approach was based on the following key industry state of the infrastructure documents:

- Canadian Infrastructure Report Card
- City of Hamilton's State of the Infrastructure reports
- Other Ontario Municipal State of the Infrastructure reports

The above reports are themselves based on established principles found within key, industry best practices documents such as:

- The National Guide for Sustainable Municipal Infrastructure (Canada)
- The International Infrastructure Management Manual (Australia / New Zealand)
- American Society of Civil Engineering Manuals (U.S.A.)

Scope: Within this State of the Infrastructure report, a high level review will be undertaken for the following asset classes:

1. **Road Network:** Urban and rural paved
2. **Bridges & Culverts:** Bridges with a span greater than 3m
3. **Water Network:** Water mains, hydrants, valves, facilities
4. **Sanitary Sewer Network:** Sanitary sewer mains, manholes, facilities
5. **Storm Sewer Network:** Storm sewer mains, catch basins, manholes

3.2 Approach

The asset classes above were reviewed at a very high level due to the nature of data and information available. Subsequent detailed reviews of this analysis are recommended on an annual basis, as more detailed conditions assessment information becomes available for each infrastructure program.

3.2.1 Base Data

In order to understand the full inventory of infrastructure assets within Prescott, all tangible capital asset data, as collected to meet the PSAB 3150 accounting standard, was loaded into the CityWide Tangible Asset™ software module. This data base now provides a detailed and summarized inventory of assets as used throughout the analysis within this report and the entire Asset Management Plan.

3.2.2 Asset Deterioration Review

The town has supplied condition data for the entire road network and all of the large bridge structures. The condition data recalculates a new performance age for each individual asset and, As such, a far more accurate prediction of future replacement can be established and applied to the future investment requirements within this AMP report.

For those assets without condition data, the sanitary, water and storm assets, the deterioration review will rely on the 'straight line' amortization schedule approach provided from the accounting data. Although

this approach is based on age data and useful life projections, and is not as accurate as the use of detailed condition data, it does provide a relatively reliable benchmark of future requirements.

3.2.3 Identify Sustainable Investment Requirements

A gap analysis was performed to identify sustainable investment requirements for each asset category. Information on current spending levels and budgets was acquired from the organization, future investment requirements were calculated, and the gap between the two was identified.

The above analysis is performed by using investment and financial planning models, and life cycle costing analysis, embedded within the CityWide software suite of applications.

3.2.4 Asset Rating Criteria

Each asset category will be rated on two key dimensions:

- **Condition vs. Performance:** Based on the condition of the asset today and how well performs its function.
- **Funding vs. Need:** Based on the actual investment requirements to ensure replacement of the asset at the right time, versus current spending levels for each asset group.

3.2.5 Infrastructure Report Card

The dimensions above will be based on a simple 1–5 star rating system, which will be converted into a letter grading system ranging from A-F. An average of the two ratings will be used to calculate the combined rating for each asset class. The outputs for all municipal assets will be consolidated within the CityWide software to produce one overall Infrastructure Report Card showing the current state of the assets.

Grading Scale: Condition vs. Performance			
What is the condition of the asset today and how well does it perform its function?			
Star Rating	Letter Grade	Color Indicator	Description
★★★★★	A		Excellent: No noticeable defects
★★★★	B		Good: Minor deterioration
★★★	C		Fair: Deterioration evident, function is affected
★★	D		Poor: Serious deterioration. Function is inadequate
★	F		Critical: No longer functional. General or complete failure

Grading Scale: Funding vs. Need		
Based on the actual investment requirements to ensure replacement of the asset at the right time, versus current spending levels for each asset group.		
Star Rating	Letter Grade	Description
★★★★★	A	Excellent: 91 to 100% of need
★★★★	B	Good: 76 to 90% of need
★★★	C	Fair: 61 to 75% of need
★★	D	Poor: 46 – 60% of need
★	F	Critical: under 45% of need

3.2.6 General Methodology and Reporting Approach

The report will be based on the seven key questions of asset management as outlined within the National Guide for Sustainable Municipal Infrastructure:

- What do you own and where is it? (inventory)
- What is it worth? (valuation / replacement cost)
- What is its condition / remaining service life? (function & performance)
- What needs to be done? (maintain, rehabilitate, replace)
- When do you need to do it? (useful life analysis)
- How much will it cost? (investment requirements)
- How do you ensure sustainability? (long-term financial plan)

The above questions will be answered for each individual asset category in the following report sections.

3.3 Road Network

A large, bold, red letter 'C' is centered within a dashed rectangular border.

INFRASTRUCTURE REPORT CARD GRADE

3.3 Road Network

3.3.1 What do we own?

As shown in the summary table below, the entire network comprises approximately 32 centreline km of road.

Road Network Inventory		
Asset Type	Asset Component	Quantity/Units
Road Network	Rural - HCB	6,415.80m.sq
	Suburban - HCB	60,031m.sq
	Urban - HCB	201,865m.sq
	Sidewalks	40,175m.sq


The road network data was extracted from the Tangible Capital Asset module of the CityWide software suite.

3.3.2 What is it worth?

The estimated replacement value of the road network, in 2012 dollars, is approximately \$20 million. The cost per household for the road network is \$9,181 based on 2,155 households.

Road Network Replacement Value				
Asset Type	Asset Component	Quantity/Units	2012 Unit Replacement Cost	2012 Overall Replacement Cost
Road Network	Rural - HCB	6,415.80m.sq	NRBCPI	\$389,440
	Suburban - HCB	60,031m.sq	NRBCPI	\$2,823,469
	Urban - HCB	201,865m.sq	\$61	\$12,313,765
	Sidewalks	40,175m.sq	\$106	\$4,258,550
				\$19,785,224


The pie chart below provides a breakdown of each of the network components to the overall system value.



3.3.3 What condition is it in?

The vast majority, 87%, of the municipality's road network is in fair to excellent condition, with the remaining 13% in poor to critical condition. As such, the municipality received a Condition vs. Performance rating of 'B'.

Road and Sidewalk Network Condition by Area (m.sq)



3.3.4 What do we need to do to it?

There are generally four distinct phases in an asset's life cycle that require specific types of attention and lifecycle activity. These are presented at a high level for the road network below. Further detail is provided in the "Asset Management Strategy" section of this AMP.


Addressing Asset Needs		
Phase	Lifecycle Activity	Asset Life Stage
Minor maintenance	Activities such as inspections, monitoring, sweeping, winter control, etc.	1 st Qtr
Major maintenance	Activities such as repairing pot holes, grinding out roadway rutting, and patching sections of road.	2 nd Qtr
Rehabilitation	Rehabilitation activities such as asphalt overlays, mill and paves, etc.	3 rd Qtr
Replacement	Full road reconstruction	4 th Qtr

3.3.5 When do we need to do it?

For the purpose of this report, 'useful life' data for each asset class was obtained from the accounting data within the CityWide software database. This proposed useful life is used to determine replacement needs of

individual assets. These needs are calculated and quantified in the system as part of the overall financial requirements.

Asset Useful Life in Years		
Asset Type	Asset Component	Useful Life
Road Network	Rural - HCB	40
	Suburban - HCB	40
	Urban - HCB	40
	Sidewalks	15




3.3.6 How much money do we need?

The analysis completed to determine capital revenue requirements was based on the following constraints and assumptions:

1. Replacement costs are based upon the unit costs identified within the "What is it worth?" section.
2. The timing for individual road replacement was defined by the replacement year as described in the "When do you need to do it?" section.
3. All values are presented in 2012 dollars.
4. The analysis was run for a 50 year period to ensure all assets went through at least one iteration of replacement, therefore providing a sustainable projection.

3.3.7 How do we reach sustainability?

Based upon the above parameters, the average annual revenue required to sustain Prescott's paved road network is approximately **\$685,000**. Based on Prescott's current annual funding of **\$339,000**, there is an annual **deficit of \$346,000**. Given this deficit, the municipality received a Funding vs. Need rating of 'D'. The following graph illustrates the expenditure requirements in five year increments against the sustainable funding threshold line.



In conclusion, based on field condition assessment data, the road network is generally in very good condition, however, with some assets at the end of their useful lives. There are replacement needs to be addressed within the next 5 years totaling approximately \$4 million. It should be noted, however, that the useful life for sidewalks is projected at 15 years, while industry standards are usually closer to 50 years. Increasing the useful life will reduce the immediate requirements listed above. In addition, the condition assessment data, along with risk management strategies, should be reviewed together to aid in prioritizing overall needs for rehabilitation and replacement and assist with optimizing the long and short term budgets. Further detail is outlined within the "Asset Management Strategy" section of this AMP.

3.3.8 Recommendations

The municipality received an overall rating of 'C' for its road network, calculated from the Condition vs. Performance and the Funding vs. Need ratings. Accordingly, we recommend the following:

1. The condition assessment data, along with risk management strategies, should be reviewed together to aid in prioritizing overall needs for rehabilitation and replacement.
2. A tailored life cycle activity framework should be also be developed by the Town as outlined further within the "Asset Management Strategy" section of this AMP.
3. The useful life projections used by the municipality should be reviewed for consistency with industry standards.
4. Once the above studies are complete or underway, the data should be loaded into the CityWide software and an updated "current state of the infrastructure" analysis should be generated.
5. An appropriate % of asset replacement value should be used for operations and maintenance activities on an annual basis. This should be determined through a detailed analysis of O & M activities and be added to future AMP reporting.
6. The Infrastructure Report Card should be updated on an annual basis.

3.5 Bridges & Culverts



3.5 Bridges & Culverts

3.5.1 What do we own?

As shown in the summary table below, the municipality owns 1 bridge with a span greater than 3m

Bridges & Culverts Inventory		
Asset Type	Asset Component	Quantity/Units
Bridges	Bridge	939.89m.sq


3.5.2 What is it worth?

The estimated replacement value of the municipality's bridges & culverts, in 2012 dollars, is approximately \$5.5 million. The cost per household for bridges & culverts is \$2,535 based on 2,155 households.

Bridges & Culverts Replacement Value				
Asset Type	Asset Component	Quantity/Units	2012 Unit Replacement Cost	2012 Replacement Cost
Bridges	Bridge	939.89m.sq	User-Defined	\$5,463,634
				\$5,463,634

3.5.3 What condition is it in?

All 100% of the municipality's bridges & culverts are in good condition. As such, the municipality received a Condition vs. Performance rating of 'B'.



3.5.4 What do we need to do to it?

There are generally four distinct phases in an asset's life cycle. These are presented at a high level for the bridge and culvert structures below. Further detail is provided in the "Asset Management Strategy" section of this AMP.


Addressing Asset Needs		
Phase	Lifecycle Activity	Asset Life Stage
Minor Maintenance	Activities such as inspections, monitoring, sweeping, winter control, etc.	1 st Qtr
Major Maintenance	Activities such as repairs to cracked or spalled concrete, damaged expansion joints, bent or damaged railings, etc.	2 nd Qtr
Rehabilitation	Rehabilitation events such as structural reinforcement of structural elements, deck replacements, etc.	3 rd Qtr
Replacement	Full structure reconstruction	4 th Qtr

3.5.5 When do we need to do it?

For the purpose of this report, 'useful life' data for each asset class was obtained from the accounting data within the CityWide software database. This proposed useful life is used to determine replacement needs of individual assets, which are calculated in the system as part of the overall financial requirements.

Asset Useful Life in Years		
Asset Type	Asset Component	Useful Life in Years
Bridges & Culverts	Bridges	40

The following graph shows the current projection of structure replacements based on the age of the asset only.




3.5.6 How much money do we need?

The analysis completed to determine capital revenue requirements was based on the following constraints and assumptions:

1. Replacement costs are based upon the "What is it worth?" section above.
2. The timing for individual structure replacement was defined by the replacement year as described in the "When do you need to do it?" section above.
3. All values are presented in 2012 dollars.
4. The analysis was run for a 75 year period to ensure all assets cycled through at least one iteration of replacement, therefore providing a sustainable projection.

3.5.7 How do we reach sustainability?

Based upon the above assumptions, the average annual revenue required to sustain Prescott's bridges & culverts is **\$188,000**. Based on Prescott's current annual funding of **\$1,000**, there is an annual **deficit of \$187,000**. As such, the municipality received a Funding vs. Need rating of 'F'. The following graph presents five year blocks of expenditure requirements against the sustainable funding threshold line.




In conclusion, based on field condition assessment data, the CNR overpass on Edward is in good condition with no immediate replacement needs.

3.5.8 Recommendations

The municipality received an overall rating of 'D' for its bridges & culverts, calculated from the Condition vs. Performance and the Funding vs. Need ratings. Accordingly, we recommend the following:

1. An appropriate % of asset replacement value should be used for operations and maintenance activities on an annual basis. This should be determined through a detailed analysis of O & M activities and added to future AMP reporting.
2. The Infrastructure Report Card should be updated on an annual basis.

3.6 Water Network



3.6 Water Network

3.6.1 What do we own?

Prescott is responsible for the following water network inventory which includes approximately 31 km of water mains:

Water Network Inventory		
Asset Type	Asset Component	Quantity
Water Network	Mains - Local (15mm)	45m
	Mains - Local (25mm)	136m
	Mains - Local (100mm)	820m
	Mains - Local (150mm)	14,088m
	Mains - Local (200mm)	7,273m
	Mains - Local (250mm)	2,195m
	Mains - Local (300mm)	5,960m
	Mains - Local (400mm)	703m
	House Services	1,741
	Fire Hydrant	205
	Valve	373
	Water Facilities	4


The water network data was extracted from the Tangible Capital Asset module of the CityWide software suite.

3.6.2 What is it worth?

The estimated replacement value of the water network, in 2012 dollars, is approximately \$31 million. The cost per household for the water network is \$14,193 based on 2,155 households.


Water Network Replacement Value				
Asset Type	Asset Component	Quantity	2012 Unit Replacement Cost	2012 Overall Replacement Cost
Water Network	Mains - Local (15mm)	45m	NRBCPI	\$7,751
	Mains - Local (25mm)	136m	NRBCPI	\$26,847
	Mains - Local (100mm)	820m	NRBCPI	\$62,629
	Mains - Local (150mm)	14,088m	NRBCPI	\$2,592,979
	Mains - Local (200mm)	7,273m	\$374	\$2,720,102
	Mains - Local (250mm)	2,195m	NRBCPI	\$522,915
	Mains - Local (300mm)	5,960m	\$342	\$2,038,320
	Mains - Local (400mm)	703m	NRBCPI	\$252,105
	House Services	1,741	\$2,926	\$5,094,166
	Fire Hydrant	205	\$5,650	\$1,158,250
	Valve	373	\$3,975	\$1,482,675
	Water Facilities	4	NRBCPI	\$14,619,164
	Mains - Local (15mm)	45m	NRBCPI	\$7,751
				\$30,585,654

The pie chart below provides a breakdown of each of the network components to the overall system value.




3.6.3 What condition is it in?

More than 2/3 of the municipality's water mains are in poor to critical condition. Based on replacement cost, however, 100% of the water facilities are in fair to good (66%) condition. with the remaining in poor to critical condition. In addition, 40% of the appurtenances are in poor to critical condition, with the remaining in fair to excellent condition. As such, the municipality received a Condition vs. Performance rating of 'C'.



Water Facilities Condition by Replacement Value (\$)



3.6.4 What do we need to do to it?

There are generally four distinct phases in an asset's life cycle. These are presented at a high level for the water network below. Further detail is provided in the "Asset Management Strategy" section of this AMP.

Addressing Asset Needs		
Phase	Lifecycle Activity	Asset Age
Minor Maintenance	Activities such as inspections, monitoring, cleaning and flushing, hydrant flushing, pressure tests, visual inspections, etc.	1st Qtr
Major Maintenance	Such events as repairing water main breaks, repairing valves, replacing individual small sections of pipe etc.	2nd Qtr
Rehabilitation	Rehabilitation events such as structural lining of pipes and a cathodic protection program to slow the rate of pipe deterioration.	3rd Qtr
Replacement	Pipe replacements	4th Qtr


3.6.5 When do we need to do it?

For the purpose of this report "useful life" data for each asset class was obtained from the accounting data within the CityWide software database. This proposed useful life is used to determine replacement needs of individual assets, which are calculated in the system as part of the overall financial requirements.

Asset Useful Life in Years		
Asset Type	Asset Component	Useful Life in Years
Water Network	Mains - Local (15mm)	60
	Mains - Local (25mm)	60
	Mains - Local (100mm)	60
	Mains - Local (150mm)	60
	Mains - Local (200mm)	60
	Mains - Local (250mm)	60
	Mains - Local (300mm)	60
	Mains - Local (400mm)	60
	House Services	80
	Fire Hydrant	50
	Valve	80
	Water Facilities	60

As field condition information becomes available in time, the data should be loaded into the CityWide system in order to increasingly have a more accurate picture of current asset age and condition, therefore, future replacement requirements. The following graph shows the current projection of water main replacements based on the age of the assets only.

Water Main Replacement Profile




3.6.6 How much money do we need?

The analysis completed to determine capital revenue requirements was based on the following assumptions:

1. Replacement costs are based upon the unit costs identified within the "What is it worth?" section above.
2. The timing for individual water main replacement was defined by the replacement year as described in the "When do you need to do it?" section above.
3. All values are presented in 2012 dollars.
4. The analysis was run for a 100 year period to ensure all assets went through at least one iteration of replacement, therefore providing a sustainable projection.

3.6.7 How do we reach sustainability?

Based upon the above assumptions, the average annual revenue required to sustain Prescott's water network is approximately **\$421,000**. Based on Prescott's current annual funding of **\$241,000**, there is a **deficit of \$180,000**. As such, the municipality received a Funding vs. Need rating of 'D'. The following graph presents five year blocks of expenditure requirements against the sustainable funding threshold line.



In conclusion, Prescott's water distribution network has a significant number of water mains in critical condition based on age data only. There are replacement needs totaling approximately \$3 million in the next 5 years. It should be noted, however, that the useful life for water mains is projected at 60 years, while industry standards are usually 80 - 90 years. Increasing the useful life will reduce the immediate requirements listed above. In addition, a study to better understand field condition should be implemented to optimize the short and long term budgets based on actual need. This is discussed further in the Asset Management Strategy portion of this Asset Management Plan.

3.6.8 Recommendations

The municipality received an overall rating of 'D+' for its water network, calculated from the Condition vs. Performance and the Funding vs. Need ratings. Accordingly, we recommend the following:

1. A more detailed study to define the current condition of the water network should be undertaken as described further within the "Asset Management Strategy" section of this AMP.
2. The useful life projections used by the municipality should be reviewed for consistency with industry standards.
3. Once the above studies are complete, a new performance age should be applied to each water main and an updated "current state of the infrastructure" analysis should be generated.
4. An appropriate % of asset replacement value should be used for operations and maintenance activities on an annual basis. This should be determined through a detailed analysis of O & M activities and be added to future AMP reporting.
5. The Infrastructure Report Card should be updated on an annual basis.

3.7 Sanitary Sewer Network



3.7 Sanitary Sewer Network

3.7.1 What do we own?

The inventory components of the sanitary sewer network are outlined in the table below. The entire Network consists of approximately 31 km of sewer main.

Sanitary Sewer Inventory		
Asset Type	Asset Component	Quantity
Sanitary Sewer Network	Mains - Local (150mm)	817.20m
	Mains - Local (200mm)	6,370.20m
	Mains - Local (250mm)	12,313.60m
	Mains - Local (300mm)	5,710.10m
	Mains - Local (350mm)	457m
	Mains - Local (400mm)	2,240m
	Mains - Local (450mm)	120m
	Mains - Local (600mm)	505m
	Mains - Local (675mm)	354.60m
	Mains - Local (750mm)	1,423.10m
	Mains - Local (900mm)	448m
	Manhole	356
Sanitary Facilities	11	


The Sanitary Sewer Network data was extracted from the Tangible Capital Asset module of the CityWide software application.

3.7.2 What is it worth?

The estimated replacement value of the sanitary sewer network, in 2012 dollars, is approximately \$43 million. The cost per household for the sanitary network is \$19,992 based on 2,155 households.


Sanitary Sewer Replacement Value				
Asset Type	Asset Component	Quantity	2012 Unit Replacement Cost	2012 Overall Replacement Cost
Sanitary Sewer Network	Mains - Local (150mm)	817.20m	NRBCPI	\$123,226
	Mains - Local (200mm)	6,370.20m	NRBCPI	\$1,438,267
	Mains - Local (250mm)	12,313.60m	NRBCPI	\$5,684,776
	Mains - Local (300mm)	5,710.10m	\$170	\$970,717
	Mains - Local (350mm)	457m	NRBCPI	\$93,621
	Mains - Local (400mm)	2,240m	NRBCPI	\$546,934
	Mains - Local (450mm)	120m	NRBCPI	\$38,591
	Mains - Local (600mm)	505m	NRBCPI	\$464,892
	Mains - Local (675mm)	354.60m	NRBCPI	\$143,466
	Mains - Local (750mm)	1,423.10m	NRBCPI	\$916,823
	Mains - Local (900mm)	448m	NRBCPI	\$511,230
	Manhole	356	\$10,860	\$3,866,160
	Sanitary Facilities	11	NRBCPI	\$28,284,081
				\$43,082,785

The pie chart below provides a breakdown of each of the network components to the overall system value.



3.7.3 What condition is it in?

The majority, 75%, of the municipality's sanitary sewer assets are in fair to excellent condition, with the remaining quarter in poor to critical condition. As such, the municipality received a Condition vs. Performance rating of 'C+'.



3.7.4 What do we need to do to it?

There are generally four distinct phases in an assets life cycle. These are presented at a high level for the sanitary sewer network below. Further detail is provided in the "Asset Management Strategy" section of this AMP.

Addressing Asset Needs		
Phase	Lifecycle Activity	Asset Life Stage
Minor Maintenance	Activities such as inspections, monitoring, cleaning and flushing, zoom camera and CCTV inspections, etc.	1 st Qtr
Major Maintenance	Activities such as repairing manholes and replacing individual small sections of pipe.	2 nd Qtr
Rehabilitation	Rehabilitation events such as structural lining of pipes are extremely cost effective and provide an additional 75 plus years of life.	3 rd Qtr
Replacement	Pipe replacements	4 th Qtr


3.7.5 When do we need to do it?

For the purpose of this report "useful life" data for each asset class was obtained from the accounting data within the CityWide software database. This proposed useful life is used to determine replacement needs of individual assets, which are calculated in the system as part of the overall financial requirements.

Asset Useful Life in Years		
Asset Type	Asset Component	Useful Life in Years
Sanitary Sewer Network	Mains - Local (150mm)	80
	Mains - Local (200mm)	80
	Mains - Local (250mm)	80
	Mains - Local (300mm)	80
	Mains - Local (350mm)	80
	Mains - Local (400mm)	80
	Mains - Local (450mm)	80
	Mains - Local (600mm)	80
	Mains - Local (675mm)	80
	Mains - Local (750mm)	80
	Mains - Local (900mm)	80
	Manhole	80
	Sanitary Facilities	60

As field condition information becomes available in time, the data should be loaded into the CityWide system in order to increasingly have a more accurate picture of current asset performance age and, therefore, future replacement requirements. The following graph shows the current projection of sanitary sewer main replacements based on the age of the asset only.

Sanitary Sewer Main Replacement Profile




3.7.6 How much money do we need?

The analysis completed to determine capital revenue requirements was based on the following assumptions:

1. Replacement costs are based upon the unit costs identified within the "What is it worth?" section above.
2. The timing for individual sewer main replacement was defined by the replacement year as described in the "When do you need to do it?" section above.
3. All values are presented in 2012 dollars.
4. The analysis was run for a 100 year period to ensure all assets went through at least one iteration of replacement, therefore providing a sustainable projection.

3.7.7 How do we reach sustainability?

Based upon the above assumptions, the average annual revenue required to sustain Prescott's sanitary sewer network is approximately **\$716,000**. Based on Prescott's current annual funding of **\$146,000**, there is an annual **deficit of \$570,000**. As such, the municipality received a Funding vs. Need rating of 'F'. The following graph presents five year blocks of expenditure requirements against the sustainable funding threshold line.



In conclusion, the sanitary sewer network, from an age based analysis only, is generally in fair to good condition, however there are some replacement requirements within the facilities. There are needs totaling approximately \$7.5 million in the next 5 years. A condition assessment program should be established to aid in prioritizing overall needs for rehabilitation and replacement and to assist with optimizing the long and short term budgets. Further detail is outlined within the "Asset Management Strategy" section of this AMP.

3.7.8 Recommendations

The municipality received an overall rating of 'D' for its sanitary sewer network, calculated from the Condition vs. Performance and the Funding vs. Need ratings. Accordingly, we recommend the following:

1. A condition assessment program should be established for the sanitary sewer network to gain a better understanding of current condition and performance as outlined further within the "Asset Management Strategy" section of this AMP.
2. Also, a detailed study to define the current condition of the sanitary facilities and their components (structural, architectural, electrical, mechanical, process, etc.) should be undertaken, as collectively they account for 65% of the sanitary infrastructure's value.
3. Once the above studies are complete or underway, the condition data should be loaded into the CityWide software and an updated "current state of the infrastructure" analysis should be generated.
4. An appropriate % of asset replacement value should be used for operations and maintenance activities on an annual basis. This should be determined through a detailed analysis of O & M activities and be added to future AMP reporting.
5. The Infrastructure Report Card should be updated on an annual basis.

3.8 Storm Sewer Network

A large, bold, red letter 'D' is centered within a white square box that has a thin blue border. The letter is the primary visual element of the report card grade.

INFRASTRUCTURE REPORT CARD GRADE

3.8 Storm Sewer Network

3.8.1 What do we own?

The inventory components of the Storm Sewer Collection system are outlined in the table below. The entire network consists of approximately 18km of sewer mains.

Storm Sewer Network Inventory (Detailed)		
Asset Type	Asset Component	Quantity
Storm Sewer Network	Mains - Local (200mm)	126m
	Mains - Local (225mm)	131.5m
	Mains - Local (250mm)	1,403.70m
	Mains - Local (300mm)	3,576.20m
	Mains - Local (350mm)	279m
	Mains - Local (375mm)	1,894.70m
	Mains - Local (400mm)	478.10m
	Mains - Local (450mm)	3,808.90m
	Mains - Local (525mm)	720.70m
	Mains - Local (600mm)	984.90m
	Mains - Local (675mm)	346m
	Mains - Local (750mm)	941.90m
	Mains - Local (825mm)	282m
	Mains - Local (900mm)	1,459.80m
	Mains - Local (1050mm)	1,023.80m
	Mains - Local (1200mm)	112.70m
	Mains - Local (1220mm)	138.7m
		Catch basin
	Manhole	246

The storm sewer network data was extracted from the Tangible Capital Asset module of the CityWide software suite.


3.8.2 What is it worth?

The estimated replacement value of the storm sewer network, in 2012 dollars, is approximately \$12 million. The cost per household for the storm sewer network is \$5,706 based on 2,155 households.

Storm Replacement Value


Asset Type	Asset Component	Quantity	2012 Unit Replacement Cost	2012 Overall Replacement Cost
Storm Sewer Network	Mains - Local (200mm)	126m	NRBCPI	\$47,696
	Mains - Local (225mm)	131.5m	NRBCPI	\$26,918
	Mains - Local (250mm)	1,403.70m	NRBCPI	\$339,684
	Mains - Local (300mm)	3,576.20m	\$160	\$572,192
	Mains - Local (350mm)	279m	NRBCPI	\$57,621
	Mains - Local (375mm)	1,894.70m	\$246	\$466,096
	Mains - Local (400mm)	478.10m	NRBCPI	\$118,311
	Mains - Local (450mm)	3,808.90m	\$203	\$773,207
	Mains - Local (525mm)	720.70m	NRBCPI	\$453,077
	Mains - Local (600mm)	984.90m	NRBCPI	\$655,724
	Mains - Local (675mm)	346m	NRBCPI	\$291,363
	Mains - Local (750mm)	941.90m	\$357	\$336,258
	Mains - Local (825mm)	282m	NRBCPI	\$264,758
	Mains - Local (900mm)	1,459.80m	NRBCPI	\$1,191,680
	Mains - Local (1050mm)	1,023.80m	NRBCPI	\$2,289,439
	Mains - Local (1200mm)	112.70m	NRBCPI	\$179,299
	Mains - Local (1220mm)	138.7m	NRBCPI	\$343,255
		Catch basin	493	\$4,625
	Manhole	246	\$6,540	\$1,608,840
				\$12,295,544

The pie chart below provides a breakdown of each of the network components to the overall system value.



3.8.3 What condition is it in?

The vast majority, 83%, of the municipality's storm sewer mains are in fair to excellent condition. Further, nearly 90% of the appurtenances are also in fair to excellent condition. As such, the municipality received a Condition vs. Performance rating of 'C+'.



3.8.4 What do we need to do to it?

There are generally four distinct phases in an assets life cycle. These are presented at a high level for the storm sewer network below. Further detail is provided in the "Asset Management Strategy" section of this AMP.


Addressing Asset Needs		
Phase	Lifecycle Activity	Asset Age
Minor Maintenance	Activities such as inspections, monitoring, cleaning and flushing, zoom camera and CCTV inspections, etc.	1 st Qtr
Major Maintenance	Activities such as repairing manholes and replacing individual small sections of pipe.	2 nd Qtr
Rehabilitation	Rehabilitation events such as structural lining of pipes are extremely cost effective and provide an additional 75 plus years of life.	3 rd Qtr
Replacement	Pipe replacements	4 th Qtr

3.8.5 When do we need to do it?

For the purpose of this report "useful life" data for each asset class was obtained from the accounting data within the CityWide software database. This proposed useful life is used to determine replacement needs of individual assets, which are calculated in the system as part of the overall financial requirements.

Asset Useful Life in Years		
Asset Type	Asset Component	Useful Life in Years
Storm Sewer Network	Mains - Local (Less Than 450mm)	80
	Mains - Trunks (Larger Than 450mm)	80
	Catch basin	80
	Manhole	80

As field condition information becomes available in time, the data should be loaded into the CityWide system in order to increasingly have a more accurate picture of current asset performance age and, therefore, future replacement requirements. The following graph shows the current projection of storm sewer main replacements based on the age of the asset only.




3.8.6 How much money do we need?

The analysis completed to determine capital revenue requirements was based on the following assumptions:

1. Replacement costs are based upon the unit costs identified within the "What is it worth?" section above.
2. The timing for individual storm sewer main replacement was defined by the replacement year as described in the "When do you need to do it?" section above.
3. All values are presented in 2012 dollars.
4. The analysis was run for a 75 year period to ensure all assets went through one iteration of replacement, therefore providing a sustainable projection.

3.8.7 How do we reach sustainability?

Based upon the above assumptions, the average annual revenue required to sustain Prescott's storm sewer network is approximately **\$153,694**. Based on Prescott's current annual funding of **\$0**, there is an annual deficit of **\$523,000**. As such, the municipality received a Funding vs. Need rating of 'F'.



In conclusion, Prescott's storm sewer collection network, based on age data only, is generally in fair condition with very few immediate requirements.

3.8.8 Recommendations

The municipality received an overall rating of 'D' for its storm sewer network, calculated from the Condition vs. Performance and the Funding vs. Need ratings. Accordingly, we recommend the following:

1. A condition assessment program should be established for the storm sewer network to gain a better understanding of current condition and performance as outlined further within the "Asset Management Strategy" section of this AMP.
2. Once the above study is complete or underway, the condition data should be loaded into the CityWide software and an updated "current state of the infrastructure" analysis should be generated.
3. An appropriate % of asset replacement value should be used for operations and maintenance activities on an annual basis. This should be determined through a detailed analysis of O & M activities and be added to future AMP reporting.
4. The Infrastructure Report Card should be updated on an annual basis.

4.0 Infrastructure Report Card

CUMULATIVE GPA		Infrastructure Report Card		
D+		The Town of Prescott		
<ol style="list-style-type: none"> Each asset category was rated on two key, equally weighted (50/50) dimensions: Condition vs. Performance, and Funding vs. Need. See the "What condition is it in?" section for details on the grade of each asset category on the Condition vs. Performance dimension. See the "How do we reach sustainability?" section for details on the grade of each asset category on the Funding vs. Need dimension. The 'Overall Rating' below is the average of the two ratings. 				
Asset Category	Condition vs. Performance	Funding vs. Need	Overall Grade	Comments
Road Network	B	D	C	The vast majority, 87%, of the municipality's road network is in fair to excellent condition, with the remaining 13% in poor to critical condition. The average annual revenue required to sustain Prescott's paved road network is approximately \$685,000 . Based on Prescott's current annual funding of \$339,000 , there is an annual deficit of \$346,000 .
Bridges & Culverts	B	F	D	All 100% of the municipality's bridges & culverts are in good condition. The average annual revenue required to sustain Prescott's bridges & culverts is \$188,000 . Based on Prescott's current annual funding of \$1,000 , there is an annual deficit of \$187,000 .
Water Network	C	D	D+	More than 2/3 of the municipality's water mains are in poor to critical condition. Based on replacement cost, however, 100% of the water facilities are in fair to good (66%) condition, with the remaining in poor to critical condition. In addition, 40% of the appurtenances are in poor to critical condition, with the remaining in fair to excellent condition. The average annual revenue required to sustain Prescott's water network is approximately \$421,000 . Based on Prescott's current annual funding of \$241,000 , there is a deficit of \$180,000 .
Sanitary Sewer Network	C+	F	D	The majority, 75%, of the municipality's sanitary sewer assets are in fair to excellent condition, with the remaining quarter in poor to critical condition. The average annual revenue required to sustain Prescott's sanitary sewer network is approximately \$716,000 . Based on Prescott's current annual funding of \$146,000 , there is an annual deficit of \$570,000 .
Storm Sewer Network	C+	F	D	The vast majority, 83%, of the municipality's storm sewer mains are in fair to excellent condition. Further, nearly 90% of the appurtenances are also in fair to excellent condition. The average annual revenue required to sustain Prescott's storm sewer network is approximately \$153,694 . Based on Prescott's current annual funding of \$0 , there is an annual deficit of \$523,000 .

5.0 Desired Levels of Service

Desired levels of service are high level indicators, comprising many factors, as listed below, that establish defined quality thresholds at which municipal services should be supplied to the community. They support the organisation's strategic goals and are based on customer expectations, statutory requirements, standards, and the financial capacity of a municipality to deliver those levels of service.

Levels of Service are used:

- to inform customers of the proposed type and level of service to be offered;
- to identify the costs and benefits of the services offered;
- to assess suitability, affordability and equity of the services offered;
- as a measure of the effectiveness of the asset management plan
- as a focus for the AM strategies developed to deliver the required level of service

In order for a municipality to establish a desired level of service, it will be important to review the key factors involved in the delivery of that service, and the interactions between those factors. In addition, it will be important to establish some key performance metrics and track them over an annual cycle to gain a better understanding of the current level of service supplied.

Within this first Asset Management Plan, key factors affecting level of service will be outlined below and some key performance indicators for each asset type will be outlined for further review. This will provide a framework and starting point from which the municipality can determine future desired levels of service for each infrastructure class.

5.1 Key factors that influence a level of service:

- Strategic and Corporate Goals
- Legislative Requirements
- Expected Asset Performance
- Community Expectations
- Availability of Finances

5.1.1 Strategic and Corporate Goals

Infrastructure levels of service can be influenced by strategic and corporate goals. Strategic plans spell out where an organization wants to go, how it's going to get there, and helps decide how and where to allocate resources, ensuring alignment to the strategic priorities and objectives . It will help identify priorities and guide how municipal tax dollars and revenues are spent into the future. The level of importance that a community's vision is dependent upon infrastructure, will ultimately affect the levels of service provided or those levels that it ultimately aspires to deliver.

5.1.2 Legislative Requirements

Infrastructure levels of service are directly influenced by many legislative and regulatory requirements. For instance, the Safe Drinking Water Act, the Minimum Maintenance Standards for municipal highways, building codes, and the Accessibility for Ontarians with Disabilities Act are all legislative requirements that prevent levels of service from declining below a certain standard.

5.1.3 Expected Asset Performance

A level of service will be affected by current asset condition, and performance and limitations in regards to safety, capacity, and the ability to meet regulatory and environmental requirements. In addition, the design life of the asset, the maintenance items required, the rehabilitation or replacement schedule of the asset, and the total costs, are all critical factors that will affect the level of service that can be provided.

5.1.4 Community Expectations

Levels of services are directly related to the expectations that the general public has from the infrastructure. For example, the public will have a qualitative opinion on what an acceptable road looks

like, and a quantitative one on how long it should take to travel between two locations. Infrastructure costs are projected to increase dramatically in the future, therefore it is essential that the public is not only consulted, but also be educated, and ultimately make choices with respect to the service levels that they wish to pay for.

5.1.5 Availability of Finances

Availability of finances will ultimately control all aspects of a desired level of service. Ideally, these funds must be sufficient to achieve corporate goals, meet legislative requirements, address an asset's life cycle needs, and meet community expectations. Levels of service will be dictated by availability of funds or elected officials' ability to increase funds, or the community's willingness to pay.


5.2 Key Performance Indicators

Performance measures or key performance indicators (KPIs) that track levels of service should be specific, measurable, achievable, relevant, and timebound (SMART). Many good performance measures can be established and tracked through the CityWide suite of software products. In this way, through automation, results can be reviewed on an annual basis and adjustments can be made to the overall asset management plan, including the desired level of service targets.

In establishing measures, a good rule of thumb to remember is that maintenance activities ensure the performance of an asset and prevent premature aging, whereas rehab activities extend the life of an asset. Replacement activities, by definition, renew the life of an asset. In addition, these activities are constrained by resource availability (in particular, finances) and strategic plan objectives. Therefore, performance measures should not just be established for operating and maintenance activities, but also for the strategic, financial, and tactical levels of the asset management program. This will assist all levels of program delivery to review their performance as part of the overall level of service provided.

This is a very similar approach to the "balanced score card" methodology, in which financial and non-financial measures are established and reviewed to determine whether current performance meets expectations. The "balanced score card", by design, links day to day operations activities to tactical and strategic priorities in order to achieve an overall goal, or in this case, a desired level of service.

The structure of accountability and level of indicator with this type of process is represented in the following table, modified from the InfraGuide's best practice document, "Developing Indicators and Benchmarks" published in April 2003.



As a note, a caution should be raised over developing too many performance indicators that may result in data overload and lack of clarity. It is better to develop a select few that focus in on the targets of the asset management plan.

Outlined below for each infrastructure class is a suggested service description, suggested service scope, and suggested performance indicators. These should be reviewed and updated in each iteration of the AMP.

5.3 Transportation Services

5.3.1 Service Description

The Town's transportation network comprises approximately 32 centreline km of road, and also includes 1 large bridge, and the associated curbs, lane markings, and sidewalks.

Together, the above infrastructure enables the municipality to deliver transportation and pedestrian facility services and give people a range of options for moving about in a safe and efficient manner.

5.3.2 Scope of Services

- **Movement** – providing for the movement of people and goods.
- **Access** – providing access to residential, commercial, and industrial properties and other community amenities.
- **Recreation** – providing for recreational use, such as walking, cycling, or special events such as parades.

5.3.3 Performance Indicators (reported annually)

Performance Indicators (reported annually)	
Strategic Indicators	<ul style="list-style-type: none"> ■ percentage of total reinvestment compared to asset replacement value ■ completion of strategic plan objectives (related to transportation)
Financial Indicators	<ul style="list-style-type: none"> ■ annual revenues compared to annual expenditures ■ annual replacement value depreciation compared to annual expenditures ■ total cost of borrowing compared to total cost of service ■ revenue required to maintain annual network growth
Tactical Indicators	<ul style="list-style-type: none"> ■ percentage of road network rehabilitated / reconstructed ■ value of bridge / large culvert structures rehabilitated or reconstructed ■ overall road condition index as a percentage of desired condition index ■ overall bridge condition index as a percentage of desired condition index ■ annual adjustment in condition indexes ■ annual percentage of network growth ■ percent of paved road lane km where the condition is rated poor or critical ■ number of bridge / large culvert structures where the condition is rated poor or critical ■ percentage of road network replacement value spent on operations and maintenance ■ percentage of bridge / large culvert structures replacement value spent on operations and maintenance
Operational Indicators	<ul style="list-style-type: none"> ■ percentage of road network inspected within last 5 years ■ percentage of bridge / large culvert structures inspected within last two years ■ operating costs for paved roads per lane km ■ operating costs for gravel roads per lane km ■ operating costs for bridge / large culvert structures per square metre ■ number of customer requests received annually ■ percentage of customer requests responded to within 24 hours

5.4 Water / Sanitary / Storm Networks

5.4.1 Service Description

The Town's water distribution network comprises 31 km of water main, 205 hydrants and 4 facilities. The waste water network comprises 31 km of sanitary sewer main, 356 manholes and 11 facilities. The storm water network comprises 18 km of storm main, 246 manholes and 493 catch basins.

Together, the above infrastructure enables the municipality to deliver a potable water distribution service, and a waste water and storm water collection service to the residents of the municipality.

5.4.2 Scope of services

- The provision of clean safe drinking water through a distribution network of water mains and pumps.
- The removal of waste water through a collection network of sanitary sewer mains.
- The removal of storm water through a collection network of storm sewer mains, and catch basins

5.4.3 Performance Indicators (reported annually)

Performance Indicators (reported annually)	
Strategic Indicators	<ul style="list-style-type: none"> ■ Percentage of total reinvestment compared to asset replacement value ■ Completion of strategic plan objectives (related water / sanitary / storm)
Financial Indicators	<ul style="list-style-type: none"> ■ Annual revenues compared to annual expenditures ■ Annual replacement value depreciation compared to annual expenditures ■ Total cost of borrowing compared to total cost of service ■ Revenue required to maintain annual network growth ■ Lost revenue from system outages
Tactical Indicators	<ul style="list-style-type: none"> ■ Percentage of water / sanitary / storm network rehabilitated / reconstructed ■ Overall water / sanitary / storm network condition index as a percentage of desired condition index ■ Annual adjustment in condition indexes ■ Annual percentage of growth in water / sanitary / storm network ■ Percentage of mains where the condition is rated poor or critical for each network ■ Percentage of water / sanitary / storm network replacement value spent on operations and maintenance
Operational Indicators	<ul style="list-style-type: none"> ■ Percentage of water / sanitary / storm network inspected ■ Operating costs for the collection of wastewater per kilometre of main. ■ Number of wastewater main backups per 100 kilometres of main ■ Operating costs for storm water management (collection, treatment, and disposal) per kilometre of drainage system. ■ Operating costs for the distribution/ transmission of drinking water per kilometre of water distribution pipe. ■ Number of days when a boil water advisory issued by the medical officer of health, applicable to a municipal water supply, was in effect. ■ Number of water main breaks per 100 kilometres of water distribution pipe in a year. ■ Number of customer requests received annually per water / sanitary / storm networks ■ Percentage of customer requests responded to within 24 hours per water / sanitary / storm network

6.0 Asset Management Strategy

6.1 Objective

To outline and establish a set of planned actions, based on best practice, that will enable the assets to provide a desired and sustainable level of service, while managing risk, at the lowest life cycle cost.

The Asset Management Strategy will develop an implementation process that can be applied to the needs identification and prioritization of renewal, rehabilitation, and maintenance activities. This will assist in the production of a 10 year plan, including growth projections, to ensure the best overall health and performance of the municipality's infrastructure.

This section includes an overview of condition assessment techniques for each asset class; the life cycle interventions required, including interventions with the best ROI; and prioritization techniques, including risk, to determine which priority projects should move forward into the budget first.

6.2 Non-Infrastructure Solutions and Requirements

The municipality should explore, as requested through the provincial requirements, which non-infrastructure solutions should be incorporated into the budgets for the road, water, sewer (sanitary and storm), and bridges & culverts programs. Non-Infrastructure solutions are such items as studies, policies, condition assessments, consultation exercises, etc., that could potentially extend the life of assets or lower total asset program costs in the future.

Typical solutions for a municipality include linking the asset management plan to the strategic plan, growth and demand management studies, infrastructure master plans, better integrated infrastructure and land use planning, public consultation on levels of service, and condition assessment programs. As part of future asset management plans, a review of these requirements should take place, and a portion of the capital budget should be dedicated for these items in each programs budget.

It is recommended, under this category of solutions, that the municipality implement holistic condition assessment programs for their road, water, sanitary, and storm sewer networks. This will lead to higher understanding of infrastructure needs, enhanced budget prioritization methodologies, and a clearer path of what is required to achieve sustainable infrastructure programs.

6.3 Condition Assessment Programs

The foundation of good asset management practice is based on having comprehensive and reliable information on the current condition of the infrastructure. Municipalities need to have a clear understanding regarding performance and condition of their assets, as all management decisions regarding future expenditures and field activities should be based on this knowledge. An incomplete understanding about an asset may lead to its premature failure or premature replacement.

Some benefits of holistic condition assessment programs within the overall asset management process are listed below:

- Understanding of overall network condition leads to better management practices
- Allows for the establishment of rehabilitation programs
- Prevents future failures and provides liability protection
- Potential reduction in operation / maintenance costs
- Accurate current asset valuation
- Allows for the establishment of risk assessment programs
- Establishes proactive repair schedules and preventive maintenance programs
- Avoids unnecessary expenditures

- Extends asset service life therefore improving level of service
- Improves financial transparency and accountability
- Enables accurate asset reporting which, in turn, enables better decision making

Condition assessment can involve different forms of analysis such as subjective opinion, mathematical models, or variations thereof, and can be completed through a very detailed or very cursory approach.

When establishing the condition assessment of an entire asset class, the cursory approach (metrics such as good, fair, poor, critical) is used. This will be a less expensive approach when applied to thousands of assets, yet will still provide up to date information, and will allow for detailed assessment or follow up inspections on those assets captured as poor or critical condition later.

The following section outlines condition assessment programs available for road, bridge, sewer, and water networks that would be useful for the municipality.

6.3.1 Pavement Network Inspections

Typical industry pavement inspections are performed by consulting firms using specialised assessment vehicles equipped with various electronic sensors and data capture equipment. The vehicles will drive the entire road network and typically collect two different types of inspection data – surface distress data and roughness data.

Surface distress data involves the collection of multiple industry standard surface distresses, which are captured either electronically, using sensing detection equipment mounted on the van, or visually, by the van's inspection crew. Examples of surface distresses are:

- **For asphalt surfaces**
alligator cracking; distortion; excessive crown; flushing; longitudinal cracking; map cracking; patching; edge cracking; potholes; ravelling; rippling; transverse cracking; wheel track rutting
- **For concrete surfaces**
coarse aggregate loss; corner 'C' and 'D' cracking; distortion; joint faulting; joint sealant loss; joint spalling; linear cracking; patching; polishing; potholes; ravelling; scaling; transverse cracking

Roughness data capture involves the measurement of the roughness of the road, measured by lasers that are mounted on the inspection van's bumper, calibrated to an international roughness index.

Most firms will deliver this data to the client in a database format complete with engineering algorithms and weighting factors to produce an overall condition index for each segment of roadway. This type of scoring database is ideal for upload into the CityWide software database, in order to tag each road with a present condition and then further life cycle analysis to determine what activity should be completed on which road, in what timeframe, and to calculate the cost for the work will be completed within the CityWide system.

The above process is an excellent way to capture road condition as the inspection trucks will provide detailed surface and roughness data for each road segment, and often include video or street imagery. A very rough industry estimate of cost would be about \$100 per centreline km of road, which means it would cost the municipality approximately \$3,200 for the 32 centreline km of paved road network.

Another option for a cursory level of condition assessment is for municipal road crews to perform simple windshield surveys as part of their regular patrol. Many municipalities have created data collection inspection forms to assist this process and to standardize what presence of defects would constitute a good, fair, poor, or critical score. Lacking any other data for the complete road network, this can still be seen as a good method and will assist greatly with the overall management of the road network. The CityWide Works software has a road patrol component built in that could capture this type of inspection data during road patrols in the field, enabling later analysis of rehabilitation and replacement needs for budget development.

It is recommended that the municipality establish a pavement condition assessment program and that a portion of capital funding is dedicated to this.

6.3.2 Bridges & Culverts (greater than 3m) Inspections

Ontario municipalities are mandated by the Ministry of Transportation to inspect all structures that have a span of 3 metres or more, according to the OSIM (Ontario Structure Inspection Manual). At present, in the municipality, there is 1 structure that meets this criterion.

Structure inspections must be performed by, or under the guidance of, a structural engineer, must be performed on a biennial basis (once every two years), and include such information as structure type, number of spans, span lengths, other key attribute data, detailed photo images, and structure element by element inspection, rating and recommendations for repair, rehabilitation, and replacement.

The best approach to develop a 10 year needs list for the municipality's structure portfolio would be to have the structural engineer who performs the inspections to develop a maintenance requirements report, and rehabilitation and replacement requirements report as part of the overall assignment. In addition to refining the overall needs requirements, the structural engineer should identify those structures that will require more detailed investigations and non-destructive testing techniques. Examples of these investigations are:

- Detailed deck condition survey
- Non-destructive delamination survey of asphalt covered decks
- Substructure condition survey
- Detailed coating condition survey
- Underwater investigation
- Fatigue investigation
- Structure evaluation

Through the OSIM recommendations and additional detailed investigations, a 10 year needs list will be developed for the municipality's bridges.

The 10 year needs list developed could then be further prioritized using risk management techniques to better allocate resources. Also, the results of the OSIM inspection for each structure, whether BCI (bridge condition index) or general condition (good, fair, poor, critical) should be entered into the CityWide software to update results and analysis for the development of the budget.

6.3.3 Sewer Network Inspections (Sanitary & Storm)

The most popular and practical type of sanitary and storm sewer assessment is the use of Closed Circuit Television Video (CCTV). The process involves a small robotic crawler vehicle with a CCTV camera attached that is lowered down a maintenance hole into the sewer main to be inspected. The vehicle and camera then travels the length of the pipe providing a live video feed to a truck on the road above where a technician / inspector records defects and information regarding the pipe. A wide range of construction or deterioration problems can be captured including open/displaced joints, presence of roots, infiltration & inflow, cracking, fracturing, exfiltration, collapse, deformation of pipe and more. Therefore, sewer CCTV inspection is a very good tool for locating and evaluating structural defects and general condition of underground pipes.

Even though CCTV is an excellent option for inspection of sewers it is a fairly costly process and does take significant time to inspect a large volume of pipes.

Another option in the industry today is the use of Zoom Camera equipment. This is very similar to traditional CCTV, however, a crawler vehicle is not used but in it's a place a camera is lowered down a maintenance hole attached to a pole like piece of equipment. The camera is then rotated towards each connecting pipe and the operator above progressively zooms in to record all defects and information about each pipe. The downside to this technique is the further down the pipe the image is zoomed, the less clarity is available to accurately record defects and measurement. The upside is the process is far quicker and significantly less expensive and an assessment of the manhole can be provided as well. Also, it is important to note that 80% of pipe deficiencies generally occur within 20 metres of each manhole. The following is a list of advantages of utilizing Zoom Camera technology:

- A time and cost efficient way of examining sewer systems;
- Problem areas can be quickly targeted;
- Can be complemented by a conventional camera (CCTV), if required afterwards;
- In a normal environment, 20 to 30 manholes can be inspected in a single day, covering more than 1,500 meters of pipe;
- Contrary to the conventional camera approach, cleaning and upstream flow control is not required prior to inspection;
- Normally detects 80% of pipe deficiencies, as most deficiencies generally occur within 20 meters of manholes.

The following table is based on general industry costs for traditional CCTV inspection and Zoom Camera inspection; however, costs should be verified through local contractors. It is for illustrative purposes only but supplies a general idea of the cost to inspect Prescott's entire sanitary and storm networks.

Sanitary and Sewer Inspection Cost Estimates				
Sewer Network	Assessment Activity	Cost	Metres of Main / # of Manholes	Total
Sanitary	Full CCTV	\$10 (per m)	31,000m	\$310,000
	Zoom	\$300 (per mh)	356 manholes	\$106,800
Storm	Full CCTV	\$10 (per m)	18,000m	\$180,000
	Zoom	\$300 (Per mh)	246 manholes	\$73,800

It can be seen from the above table that there is a significant cost savings achieved through the use of Zoom Camera technology. A good industry trend and best practice is to inspect the entire network using Zoom Camera technology and follow up on the poor and critical rated pipes with more detail using a full CCTV inspection. In this way, inspection expenditures are kept to a minimum, however, an accurate assessment on whether to rehabilitate or replace pipes will be provided for those with the greatest need.

It is recommended that the municipality establish a sewer condition assessment program and that a portion of capital funding is dedicated to this.

In addition to receiving a video and defect report of each pipe's CCTV or Zoom camera inspection, many companies can now provide a database of the inspection results, complete with scoring matrixes that provide an overall general condition score for each pipe segment that has been assessed. Typically pipes are scored from 1 – 5, with 1 being a relatively new pipe and 5 being a pipe at the end of its design life. This type of scoring database is ideal for upload into the CityWide software database, in order to tag each pipe with a present condition and then further life cycle analysis to determine what activity should be done to which pipe, in what timeframe, and to calculate the cost for the work will be completed by the CityWide system.

6.3.4 Water network inspections

Unlike sewer mains, it is very difficult to inspect water mains from the inside due to the high pressure flow of water constantly underway within the water network. Physical inspections require a disruption of service to residents, can be an expensive exercise, and are time consuming to set up. It is recommended practice that physical inspection of water mains typically only occurs for high risk, large transmission mains within the system, and only when there is a requirement. There are a number of high tech inspection techniques in the industry for large diameter pipes but these should be researched first for applicability as they are quite expensive. Examples are:

- Remote eddy field current (RFEC)
- Ultrasonic and acoustic techniques
- Impact echo (IE)
- Georadar

For the majority of pipes within the distribution network gathering key information in regards to the main and its environment can supply the best method to determine a general condition. Key data that could be used, along with weighting factors, to determine an overall condition score are listed below.

- Age
- Material Type
- Breaks
- Hydrant Flow Inspections
- Soil Condition

Understanding the age of the pipe will determine useful life remaining, however, water mains fail for many other reasons than just age. The pipe material is important to know as different pipe types have different design lives and different deterioration profiles. Keeping a water main break history is one of the best analysis tools to predict future pipe failures and to assist with programming rehabilitation and replacement schedules. Also, most municipalities perform hydrant flow tests for fire flow prevention purposes. The readings from these tests can also help determine condition of the associated water main. If a hydrant has a relatively poor flow condition it could be indicative of a high degree of encrustation within the attached water main, which could then be flagged as a candidate for cleaning or possibly lining. Finally, soil condition is important to understand as certain soil types can be very aggressive at causing deterioration on certain pipe types.

It is recommended that the municipality develop a rating system for the mains within the distribution network based on the availability of key data, and that funds are budgeted for this development.

Also, it is recommended that the municipality utilize the CityWide Works application to track water main break work orders and hydrant flow inspection readings as a starting point to develop a future scoring database for each water main.


6.4 AM Strategy – Life Cycle Analysis Framework

An industry review was conducted to determine which life cycle activities can be applied at the appropriate time in an asset's life, to provide the greatest additional life at the lowest cost. In the asset management industry, this is simply put as doing the right thing to the right asset at the right time. If these techniques are applied across entire asset networks or portfolios (e.g., the entire road network), the municipality could gain the best overall asset condition while expending the lowest total cost for those programs.

6.4.1 Paved Roads

The following analysis has been conducted at a fairly high level, using industry standard activities and costs for paved roads. With future updates of this Asset Management Strategy, the municipality may wish to run the same analysis with a detailed review of municipality activities used for roads and the associated local costs for those work activities. All of this information can be input into the CityWide software suite in order to perform updated financial analysis as more detailed information becomes available.

The following diagram depicts a general deterioration profile of a road with a 30 year life.



As shown above, during the road's life cycle there are various windows available for work activity that will maintain or extend the life of the asset. These windows are: maintenance; preventative maintenance; rehabilitation; and replacement or reconstruction.

The windows or thresholds for when certain work activities should be applied to also coincide approximately with the condition state of the asset as shown below:

Asset Condition and Related Work Activity: Paved Roads

Condition	Condition Range	Work Activity
excellent condition (Maintenance only phase)	100-76	<ul style="list-style-type: none"> ■ maintenance only
good Condition (Preventative maintenance phase)	75 - 51	<ul style="list-style-type: none"> ■ crack sealing ■ emulsions
fair Condition (Rehabilitation phase)	50 -26	<ul style="list-style-type: none"> ■ resurface - mill & pave ■ resurface - asphalt overlay ■ single & double surface treatment (for rural roads)
poor Condition (Reconstruction phase)	25 - 1	<ul style="list-style-type: none"> ■ reconstruct - pulverize and pave ■ reconstruct - full surface and base reconstruction
critical Condition (Reconstruction phase)	0	<ul style="list-style-type: none"> ■ critical includes assets beyond their useful lives which make up the backlog. they require the same interventions as the "poor" category above.

With future updates of this Asset Management Strategy the municipality may wish to review the above condition ranges and thresholds for when certain types of work activity occur, and adjust to better suit the municipality's work program. Also note: when adjusting these thresholds, it actually adjusts the level of service provided and ultimately changes the amount of money required. These threshold and condition ranges can be easily updated with the CityWide software suite and an updated financial analysis can be calculated. These adjustments will be an important component of future Asset Management Plans, as the Province requires each municipality to present various management options within the financing plan.

The table below outlines the costs for various road activities, the added life obtained for each, the condition range at which they should be applied, and the cost of 1 year added life for each (cost of activity / added life) in order to present an apples to apples comparison.

Road Lifecycle Activity Options

Treatment	Average Unit Cost (per sq. m)	Added Life (Years)	Condition Range	Cost Of Activity/Added Life
Urban Reconstruction	\$205	30	25 - 0	\$6.83
Urban Resurfacing	\$84	15	50 - 26	\$5.60
Rural Reconstruction	\$135	30	25 - 0	\$4.50
Rural Resurfacing	\$40	15	50 - 26	\$2.67
Double Surface Treatment	\$25	10	50 - 26	\$2.50
Routing & Crack Sealing (P.M)	\$2	3	75 - 51	\$0.67

As can be seen in the table above, preventative maintenance activities such as routing and crack sealing have the lowest associated cost (per sq. m) in order to obtain one year of added life. Of course, preventative maintenance activities can only be applied to a road at a relatively early point in the life cycle. It is recommended that the municipality engage in an active preventative maintenance program for all paved roads and that a portion of the maintenance budget is allocated to this.

Also, rehabilitation activities, such as urban and rural resurfacing or double surface treatments (tar and chip) for rural roads have a lower cost to obtain each year of added life than full reconstruction activities. It is recommended, if not in place already, that the municipality engages in an active rehabilitation program for urban and rural paved roads and that a portion of the capital budget is dedicated to this.

Of course, in order to implement the above programs it will be important to also establish a general condition score for each road segment, established through standard condition assessment protocols as previously described.

It is important to note that a "worst first" budget approach, whereby no life cycle activities other than reconstruction at the end of a roads life are applied, will result in the most costly method of managing a road network overall.

6.4.2 Gravel Roads

The life cycle activities required for these roads are quite different from paved roads. Gravel roads require a cycle of perpetual maintenance, including general re-grading, reshaping of the crown and cross section, gravel spot and section replacement, dust abatement and ditch clearing and cleaning.

Gravel roads can require frequent maintenance, especially after wet periods and when accommodating increased traffic. Wheel motion shoves material to the outside (as well as in-between travelled lanes), leading to rutting, reduced water-runoff, and eventual road destruction if unchecked. This deterioration process is prevented if interrupted early enough, simple re-grading is sufficient, with material being pushed back into the proper profile.

As a high proportion of gravel roads can have a significant impact on the maintenance budget, it is recommended that with further updates of this asset management plan the municipality study the traffic volumes and maintenance requirements in more detail for its gravel road network.

Similar studies elsewhere have found converting certain roadways to paved roads can be very cost beneficial especially if frequent maintenance is required due to higher traffic volumes. Roads within the gravel network should be ranked and rated using the following criteria:


- Usage - traffic volumes and type of traffic
- Functional importance of the roadway
- Known safety issues
- Frequency of maintenance and overall expenditures required

Through the above type of analysis, a program could be introduced to convert certain gravel roadways into paved roads, reducing overall costs, and be brought forward into the long range budget.

6.4.3 Sanitary and Storm Sewers

The following analysis has been conducted at a fairly high level, using industry standard activities and costs for sanitary and storm sewer rehabilitation and replacement. With future updates of this asset management strategy, the municipality may wish to run the same analysis with a detailed review of municipality activities used for sewer mains and the associated local costs for those work activities. All of this information can be input into the CityWide software suite in order to perform updated financial analysis as more detailed information becomes available.

The following diagram depicts a general deterioration profile of a sewer main with a 100 year life.



As shown above, during the sewer main's life cycle there are various windows available for work activity that will maintain or extend the life of the asset. These windows are: maintenance; major maintenance; rehabilitation; and replacement or reconstruction.

The windows or thresholds for when certain work activities should be applied also coincide approximately with the condition state of the asset as shown below:

Asset Condition and Related Work Activity: Sewer Main

Condition	Condition Range	Work Activity
excellent condition (Maintenance only phase)	100-76	■ maintenance only (cleaning & flushing etc.)
good Condition (Preventative maintenance phase)	75 - 51	■ manhole repairs ■ small pipe section repairs
fair Condition (Rehabilitation phase)	50 -26	■ structural relining
poor Condition (Reconstruction phase)	25 - 1	■ pipe replacement
critical Condition (Reconstruction phase)	0	■ critical includes assets beyond their useful lives which make up the backlog. they require the same interventions as the "poor" category above.

With future updates of this Asset Management Strategy the municipality may wish to review the above condition ranges and thresholds for when certain types of work activity occur, and adjust to better suit the municipality's work program. Also note: when adjusting these thresholds, it actually adjusts the level of service provided and ultimately changes the amount of money required. These threshold and condition ranges can be easily updated with the CityWide software suite and an updated financial analysis can be calculated. These adjustments will be an important component of future Asset Management Plans, as the province requires each municipality to present various management options within the financing plan.

The table below outlines the costs, by pipe diameter, for various sewer main rehabilitation (lining) and replacement activities. The columns display the added life obtained for each activity, the condition range at which they should be applied, and the cost of 1 year added life for each (cost of activity / added life) in order to present an apples to apples comparison.

Sewer Main Lifecycle Activity Options				
Category	Cost (per m)	Added Life	Condition Range	1 year Added Life Cost (Cost / Added Life)
Structural Rehab (m)				
0 - 325mm	\$174.69	75	50 - 75	\$2.33
325 - 625mm	\$283.92	75	50 - 75	\$3.79
625 - 925mm	\$1,857.11	75	50 - 75	\$24.76
> 925mm	\$1,771.34	75	50 - 75	\$23.62
Replacement (m)				
	\$475	100	76 - 100	\$4.75
325 - 625mm	\$725	100	76 - 100	\$7.25
625 - 925mm	\$900	100	76 - 100	\$9
> 925mm	\$1,475	100	76 - 100	\$14.75

As can be seen in the above table, structural rehabilitation or lining of sewer mains is an extremely cost effective industry activity and solution for pipes with a diameter less than 625mm. The unit cost of lining is approximately one third of replacement and the cost to obtain one year of added life is half the cost. For Prescott, this diameter range would account for over 90% of sanitary sewer mains and 75% of storm mains. Structural lining has been proven through industry testing to have a design life (useful life) of 75 years, however, it is believed that liners will probably obtain 100 years of life (the same as a new pipe).

For sewer mains with diameters greater than 625mm specialized liners are required and therefore the costs are no longer effective. It should be noted, however, that the industry is continually expanding its technology in this area and therefore future costs should be further reviewed for change and possible price reductions.

It is recommended, if not in place already, that the municipality engage in an active structural lining program for sanitary and storm sewer mains and that a portion of the capital budget be dedicated to this.

In order to implement the above, it will be important to also establish a condition assessment program to establish a condition score for each sewer main within the sanitary and storm collection networks, and therefore identify which pipes are good candidates for structural lining.


6.4.4 Bridges & Culverts (greater than 3m span)

The best approach to develop a 10 year needs list for the municipality's relatively small bridge structure portfolio would be to have the structural engineer who performs the inspections to develop a maintenance requirements report, a rehabilitation and replacement requirements report and identify additional detailed inspections as required. This approach is described in more detail within the "Bridges & Culverts (greater than 3m) Inspections" section above.

6.4.5 Water Network

As with roads and sewers above, the following analysis has been conducted at a fairly high level, using industry standard activities and costs for water main rehabilitation and replacement.

The following diagram depicts a general deterioration profile of a water main with an 80 year life.



As shown above, during the water main's life cycle there are various windows available for work activity that will maintain or extend the life of the asset. These windows are: maintenance; major maintenance; rehabilitation; and replacement or reconstruction.

The windows or thresholds for when certain work activities should be applied also coincide approximately with the condition state of the asset as shown below:

Asset Condition and Related Work Activity: Water Main

Condition	Condition Range	Work Activity
excellent condition (Maintenance only phase)	100-76	■ maintenance only (cleaning & flushing etc.)
good Condition (Preventative maintenance phase)	75 - 51	■ water main break repairs ■ small pipe section repairs
fair Condition (Rehabilitation phase)	50 -26	■ structural water main relining
poor Condition (Reconstruction phase)	25 - 1	■ pipe replacement
critical Condition (Reconstruction phase)	0	■ critical includes assets beyond their useful lives which make up the backlog. they require the same interventions as the "poor" category above.

Water main Lifecycle Activity Option

Category	Cost	Added Life	Condition Range	Cost of Activity / Added Life
Structural Rehab (m)				
0.0 - 0.150m	\$209.70	50	50 - 75	\$4.19
0.150 - 0.300m	\$31	50	50 - 75	\$6.30
0.300 - 0.400m	\$630	50	50 - 75	\$12.60
0.400 - 0.700m	\$1,500	50	50 - 75	\$30
0.700 m - & +	\$2,000	50	50 - 75	\$40
Replacement (m)				
0.0 - 0.150m	\$233	80	76 - 100	\$2.91
0.150 - 0.300m	\$350	80	76 - 100	\$4.38
0.300 - 0.400m	\$700	80	76 - 100	\$8.75
0.400 - 0.700m	\$1,500	80	76 - 100	\$18.75
0.700 m - & +	\$2,000	80	76 - 100	\$25

Water rehab technologies still require some digging (known as low dig technologies, due to lack of access) and are actually more expensive on a life cycle basis. However, if the road above the water main is in good condition lining avoids the cost of road reconstruction still resulting in a cost effective solution.

It should be noted, that the industry is continually expanding its technology in this area and therefore future costs should be further reviewed for change and possible price reductions.

At this time, it is recommended that the municipality only utilize water main structural lining when the road above requires rehab or no work.

6.5 Growth and Demand

Typically a municipality will have specific plans associated with population growth. It is essential that the asset management strategy should address not only the existing infrastructure, as above, but must include the impact of projected growth on defined project schedules and funding requirements. Projects would include the funding of the construction of new infrastructure, and/or the expansion of existing infrastructure to meet new demands. The municipality should enter these projects into the CityWide software in order to be included within the short and long term budgets as required. In addition, Prescott have committed to connecting the results of this AMP to their Growth Management Plan.

6.6 Project Prioritization

The above techniques and processes when established for the road, water, sewer networks and bridges will supply a significant listing of potential projects. Typically the infrastructure needs will exceed available resources and therefore project prioritization parameters must be developed to ensure the right projects come forward into the short and long range budgets. An important method of project prioritization is to rank each project, or each piece of infrastructure, on the basis of how much risk it represents to the organization.

6.6.1 Risk Matrix and Scoring Methodology

Risk within the infrastructure industry is often defined as the probability (likelihood) of failure multiplied by the consequence of that failure.

$$\text{RISK} = \text{LIKELIHOOD OF FAILURE} \times \text{CONSEQUENCE OF FAILURE}$$

The likelihood of failure relates to the current condition state of each asset, whether they are in excellent, good, fair, poor or critical condition, as this is a good indicator regarding their future risk of failure. The consequence of failure relates to the magnitude, or overall effect, that an asset's failure will cause. For instance, a small diameter water main break in a sub division may cause a few customers to have no water service for a few hours, whereby a large trunk water main break outside a hospital could have disastrous effects and would be a front page news item. The following table represents the scoring matrix for risk:

Consequence of Failure	Probability of Failure				
	1	2	3	4	5
5	110 Assets 129,286.1 m ² \$7,886,402.10	45 Assets 57,019.39 m ² . m \$9,219,277.98	34 Assets 18,509.2 m ² . m \$2,442,977.80	No Assets N/A	No Assets N/A
4	11 Assets 1,483.8 m \$2,404,876.98	10 Assets 715.6 m \$832,325.79	16 Assets 1,649.5 m \$1,255,819.92	3 Assets 287 m \$255,499.15	1 Asset 155 m \$37,116.22
3	58 Assets 24,892.7 m ² . m \$2,786,473.76	46 Assets 24,057.0 m ² . m \$2,203,939.20	38 Assets 12,182.3 m ² . m \$1,534,399.16	26 Assets 3,903.4 m ² . m \$693,044.45	28 Assets 5,111 m \$1,541,192.90
2	120 Assets 14,349.3 m ² . m \$4,923,839.24	92 Assets 13,493.2 m ² . m \$3,454,205.29	81 Assets 8,327.4 m \$2,337,590.90	54 Assets 5,371.8 m \$1,122,586.20	141 Assets 16,491 m \$3,241,367.24
1	4 Assets 483 m \$103,446.13	3 Assets 100.2 m \$19,006.92	2 Assets 310 m \$29,914.21	1 Asset 111 m \$45,850.32	14 Assets 940 m \$72,633.79

All of the municipality's assets analyzed within this asset management plan have been given both a likelihood of failure score and a consequence of failure score within the CityWide software.

The following risk scores have been developed at a high level for each asset class within the CityWide software system. It is recommended that the municipality undertake a detailed study to develop a more tailored suite of risk scores, particularly in regards to the consequence of failure, and that this be updated within the CityWide software with future updates to this Asset Management Plan.

The current scores that will determine budget prioritization currently within the system are as follows:

All assets:

The Likelihood of Failure score is based on the condition of the assets:

Likelihood of Failure: All Assets	
Asset condition	Likelihood of failure
Excellent condition	score of 1
Good condition	score of 2
Fair condition	score of 3
Poor condition	score of 4
Critical condition	score of 5

Bridges (based on valuation):

The consequence of failure score for this initial AMP is based upon the replacement value of the structure. The higher the value, probably the larger the structure and therefore probably the higher the consequential risk of failure:

Consequence of Failure: Bridges	
Replacement Value	Consequence of failure
Up to \$100k	Score of 1
\$101 to \$250k	Score of 2
\$251 to \$500k	Score of 3
\$501 to \$850k	Score of 4
\$851k and over	Score of 5

Roads (based on classification):

The consequence of failure score for this initial AMP is based upon the road classification as this will reflect traffic volumes and number of people affected.

Consequence of Failure: Roads	
Road Classification	Consequence of failure
Rural	score of 2
Sub Urban	score of 3
Urban	score of 5

Sanitary Sewer (based on diameter):

The consequence of failure score for this initial AMP is based upon pipe diameter as this will reflect potential upstream service area affected.

Consequence of Failure: Sanitary Sewer

Pipe Diameter	Consequence of failure
Less than 150mm	Score of 1
151-250mm	Score of 2
251-450mm	Score of 3
451-700mm	Score of 4
701mm and over	Score of 5

Water (based on diameter):

The consequence of failure score for this initial AMP is based upon pipe diameter as this will reflect potential service area affected.

Consequence of Failure: Water

Pipe Diameter	Consequence of Failure
Less than 100mm	Score of 1
101 – 200mm	Score of 2
201 – 300mm	Score of 3
301 – 400mm	Score of 4
401 and over	Score of 5

Storm Sewer (based on diameter):

The consequence of failure score for this initial AMP is based upon pipe diameter as this will reflect potential upstream service area affected.

Consequence of Failure: Storm Sewer


Replacement Value	Consequence of failure
Less than 200mm	Score of 1
201 – 500mm	Score of 2
501 – 800mm	Score of 3
801 – 1200mm	Score of 4
1,201mm and over	Score of 5

7.0 Financial Strategy

7.1 General overview of financial plan requirements

In order for an AMP to be effectively put into action, it must be integrated with financial planning and long-term budgeting. The development of a comprehensive financial plan will allow Prescott to identify the financial resources required for sustainable asset management based on existing asset inventories, desired levels of service and projected growth requirements.

The following pyramid depicts the various cost elements and resulting funding levels that should be incorporated into AMP's that are based on best practices.



This report develops such a financial plan by presenting several scenarios for consideration and culminating with final recommendations. As outlined below, the scenarios presented model different combinations of the following components:

- a) the financial requirements (as documented in the SOTI section of this report) for:
 - existing assets
 - existing service levels
 - requirements of contemplated changes in service levels (none identified for this plan)
 - requirements of anticipated growth (none identified for this plan)
- b) use of traditional sources of municipal funds:
 - tax levies
 - user fees
 - reserves
 - debt (no additional debt required for this AMP)
 - development charges (not applicable)

- c) use of non-traditional sources of municipal funds:
 - reallocated budgets (not required for this AMP)
 - partnerships (not applicable)
 - procurement methods (no changes recommended)
- d) use of senior government funds:
 - gas tax
 - grants (not included in this plan due to Provincial requirements for firm commitments)

If the financial plan component of an AMP results in a funding shortfall, the Province requires the inclusion of a specific plan as to how the impact of the shortfall will be managed. In determining the legitimacy of a funding shortfall, the Province may evaluate a municipality's approach to the following:

- a) in order to reduce financial requirements, consideration has been given to revising service levels downward
- b) all asset management and financial strategies have been considered. For example:
 - if a zero debt policy is in place, is it warranted? If not, the use of debt should be considered.
 - do user fees reflect the cost of the applicable service? If not, increased user fees should be considered.

This AMP includes recommendations that avoid long-term funding deficits.

7.2 Financial information relating to Prescott's AMP

7.2.1 Funding objective

We have developed scenarios that would enable Prescott to achieve full funding within 5 to 10 years for the following assets:

- a) **Tax funded assets:** Road Network; Bridges & Culverts; Storm Sewer Network
- b) **Rate funded assets:** Sanitary Sewer Network; Water Network

Note: For the purposes of this AMP, we have excluded the category of gravel roads since gravel roads are a perpetual maintenance asset and end of life replacement calculations do not normally apply. If gravel roads are maintained properly, they, in essence, could last forever.

For each scenario developed we have included strategies, where applicable, regarding the use of tax revenues, user fees, reserves and debt.

7.3 Tax funded assets

7.3.1 Current funding position

Tables 1 and 2 outline, by asset category, Prescott's average annual asset investment requirements, current funding positions, and funding increases required to achieve full funding on assets funded by taxes.

Asset Category	Average Annual Investment Required	2013 Annual Funding Available			Total Funding Available	Annual Deficit/Surplus
		Taxes	Gas Tax	Other		
Road Network	685,000	163,000	176,000	0	339,000	346,000
Bridges & Culverts	188,000	1,000	0	0	1,000	187,000
Storm Sewer Network	154,000	10,000	60,000	0	70,000	84,000
Total	1,027,000	174,000	236,000	0	410,000	617,000

7.3.2 Recommendations for full funding

The average annual investment requirement for paved roads, bridges & culverts, and storm sewers is \$1,027,000. Annual revenue currently allocated to these assets for capital purposes is \$410,000 leaving an annual deficit of \$617,000. To put it another way, these infrastructure categories are currently funded at 40% of their long-term requirements.

In 2013, Prescott has annual tax revenues of \$5,023,000. As illustrated in table 2, without consideration of any other sources of revenue, full funding would require the following tax increase over time:

Asset Category	Tax Increase Required for Full Funding
Road Network	6.9%
Bridges & Culverts	3.7%
Storm Sewer Network	1.7%
Total	12.3%

As outlined in section 7.4 below, there is \$20,000 of gas tax revenues currently being allocated to rate based categories. Unless there is a compelling reason not to (such as economic development strategies), we are recommending that this revenue be reallocated to the tax based categories in this section of the report so that rates fully fund rate based services in the long-term.

As illustrated in table 9, Prescott's debt payments for these asset categories will be decreasing by \$32,000 from 2013 to 2017 (5 years). Although not illustrated, debt payments will also decrease by \$32,000 from 2013 to 2022 (10 years). Our recommendations include capturing those decreases in cost and allocating them to the infrastructure deficit outlined above.

Table 3 outlines these concepts and presents a number of options:

	Without Reallocation of Gas Taxes		With Reallocation of Gas Taxes	
	5 Years	10 Years	5 Years	10 Years
Infrastructure Deficit as Outlined in Table 1	617,000	617,000	617,000	617,000
Reallocation of Gas Tax Revenue	0	0	-20,000	-20,000
Change in Debt Costs	-32,000	-32,000	-32,000	-32,000
Resulting Infrastructure Deficit	585,000	585,000	565,000	565,000
Resulting Tax Increase Required:				
Total Over Time	11.6%	11.6%	11.2%	11.2%
Annually	2.3%	1.2%	2.2%	1.1%

Considering all of the above information, we recommend the 10 year option in table 3 that includes both of the above reallocations. This involves full funding being achieved over 10 years by:

- f) over the phase-in period, reallocating the \$20,000 of gas tax revenue currently being allocated to rate funded asset categories (as listed in section 7.4 of this report) to the tax funded asset categories as outlined above.
- g) when realized, reallocating the debt cost reductions of \$32,000 to the infrastructure deficit as outlined above.

- h) increasing tax revenues by 1.1% each year for the next 10 years solely for the purpose of phasing in full funding to the asset categories covered in this section of the AMP.
- i) allocating the \$196,000 of gas tax revenue to the tax funded asset categories.
- j) increasing existing and future infrastructure budgets by the applicable inflation index on an annual basis in addition to the deficit phase-in.

Notes:

- 1. As in the past, periodic senior government infrastructure funding will most likely be available during the phase-in period. By Provincial AMP rules, this funding cannot be incorporated into the AMP unless there are firm commitments in place.

Although this option achieves full funding on an annual basis in 10 years and provides financial sustainability over the period modeled (to 2050), the recommendations do require prioritizing capital projects to fit the resulting annual funding available. As of 2013, age based data shows a pent up investment demand of \$3,731,000 for paved roads, \$0 for bridges & culverts, and \$9,000 for storm sewers. Prioritizing future projects will require the age based data to be replaced by condition based data. Although our recommendations include no further use of debt, the results of the condition based analysis may require otherwise.

7.4 Rate funded assets

7.4.1 Current funding position

Tables 4 and 5 outline, by asset category, Prescott's average annual asset investment requirements, current funding positions and funding increases required to achieve full funding on assets funded by rates.

Asset Category	Average Annual Investment Required	2013 Annual Funding Available				Annual Deficit/Surplus
		Rates	Less: Allocated to Operations	Federal Gas Tax (see note below)	Total Funding Available	
Sanitary Sewer Network	716,000	1,482,000	-1,356,000	20,000	146,000	570,000
Water Network	421,000	1,245,000	-1,004,000	0	241,000	180,000
Total	1,137,000	2,727,000	-2,360,000	20,000	387,000	750,000

7.4.2 Recommendations for full funding

The average annual investment requirement for sanitary services and water services is \$1,137,000. Annual revenue currently allocated to these assets for capital purposes is \$387,000 leaving an annual deficit of \$750,000. To put it another way, these infrastructure categories are currently funded at 34% of their long-term requirements.

In 2013, Prescott has annual sanitary revenues of \$1,482,000 and annual water revenues of \$1,245,000. As illustrated in table 5, without consideration of any other sources of revenue, full funding would require the following increases over time:

Asset Category	Rate Increase Required for Full Funding
Sanitary Sewer Network	38.5%
Water Network	14.5%

As illustrated in table 4, there are \$20,000 of gas tax revenues currently being allocated to rate based categories. Unless there is a compelling reason not to (such as economic development strategies), we are recommending that this revenue be reallocated to the tax based categories in section 7.3 above so that rates fully fund rate based services in the long-term.

As illustrated in table 9, Prescott's debt payments for sanitary services will be decreasing by \$140,000 from 2013 to 2017 (5 years). Although not illustrated, debt payments for sanitary services will be decreasing by \$472,000 from 2013 to 2022 (10 years). For water services, the amounts are \$23,000 and \$23,000 respectively. Our recommendations include capturing those decreases in cost and allocating them to the applicable infrastructure deficit.

Tables 6a and 6b outline these concepts and present a number of options:

	Sanitary Sewer Network		Water Network	
	5 Years	10 Years	5 Years	10 Years
Infrastructure Deficit as Outlined in Table 4	570,000	570,000	180,000	180,000
Reallocation of Gas Tax Revenue	0	0	0	0
Change in Debt Costs	-140,000	-472,000	-23,000	-23,000
Resulting Infrastructure Deficit	430,000	98,000	157,000	157,000
Resulting Rate Increase Required:				
Total Over Time	29.0%	6.6%	12.6%	12.6%
Annually	5.8%	0.7%	2.5%	1.3%

	Sanitary Sewer Network		Water Network	
	5 Years	10 Years	5 Years	10 Years
Infrastructure Deficit as Outlined in Table 4	570,000	570,000	180,000	180,000
Reallocation of Gas Tax Revenue	20,000	20,000	0	0
Change in Debt Costs	-140,000	-472,000	-23,000	-23,000
Resulting Infrastructure Deficit	450,000	118,000	157,000	157,000
Resulting Rate Increase Required:				
Total Over Time	30.4%	8.0%	12.6%	12.6%
Annually	6.1%	0.8%	2.5%	1.3%

Considering all of the above information, we recommend the 10 year option in table 6 that includes both reallocations. This involves full funding being achieved over 10 years by:

- d) over the phase-in period, reallocating the gas tax revenue of \$20,000 currently being allocated to sanitary services to the tax funded asset categories in section 7.3 of this report.
- e) when realized, reallocating the debt cost reductions of \$472,000 for sanitary services and \$23,000 for water services to the applicable infrastructure deficit.
- f) increasing rate revenues by 0.8% for sanitary services and 1.3% for water services each year for the next 10 years solely for the purpose of phasing in full funding to the asset categories covered in this section of the AMP.

- g) increasing existing and future infrastructure budgets by the applicable inflation index on an annual basis in addition to the deficit phase-in.

Notes:

1. As in the past, periodic senior government infrastructure funding will most likely be available during the phase-in period. By Provincial AMP rules, this funding cannot be incorporated into an AMP unless there are firm commitments in place.
2. Any increase in rates required for operations would be in addition to the above recommendations.

Although this option achieves full funding on an annual basis in 10 years and provides financial sustainability over the period modeled (to 2050), the recommendations do require prioritizing capital projects to fit the resulting annual funding available. As of 2013, age based data shows a pent up investment demand of \$7,514,000 for sanitary services and \$2,982,000 for water services. Prioritizing future projects will require the age based data to be replaced by condition based data. Although our recommendations include no further use of debt, the results of the condition based analysis may require otherwise.

7.5 Use of debt

For reference purposes, table 7 outlines the premium paid on a project if financed by debt. For example, a \$1M project financed at 3.0%¹ over 15 years would result in a 26% premium or \$260,000 of increased costs due to interest payments. For simplicity, the table does not take into account the time value of money or the effect of inflation on delayed projects.


Table 7. Total Interest Paid as a % of Project Costs

Interest Rate	Number of Years Financed					
	5	10	15	20	25	30
7.0%	22%	42%	65%	89%	115%	142%
6.5%	20%	39%	60%	82%	105%	130%
6.0%	19%	36%	54%	74%	96%	118%
5.5%	17%	33%	49%	67%	86%	106%
5.0%	15%	30%	45%	60%	77%	95%
4.5%	14%	26%	40%	54%	69%	84%
4.0%	12%	23%	35%	47%	60%	73%
3.5%	11%	20%	30%	41%	52%	63%
3.0%	9%	17%	26%	34%	44%	53%
2.5%	8%	14%	21%	28%	36%	43%
2.0%	6%	11%	17%	22%	28%	34%
1.5%	5%	8%	12%	16%	21%	25%
1.0%	3%	6%	8%	11%	14%	16%
0.5%	2%	3%	4%	5%	7%	8%
0.0%	0%	0%	0%	0%	0%	0%

It should be noted that current interest rates are near all-time lows. Sustainable funding models that include debt need to incorporate the risk of rising interest rates. The following graph shows where historical lending rates have been:

¹ Current municipal Infrastructure Ontario rates for 15 year money is 3.2%.

Historical Prime Business Interest Rate



As illustrated in table 7, a change in 15 year rates from 3% to 6% would change the premium from 26% to 54%. Such a change would have a significant impact on a financial plan.

Tables 8 and 9 outline how Prescott has historically used debt for investing in the asset categories as listed. There is currently \$8,774,000 of debt outstanding for the assets covered by this AMP. In terms of overall debt capacity, Prescott currently has \$11,315,000 of total outstanding debt and \$1,274,000 of total annual principal and interest payment commitments. These principal and interest payments are well within its provincially prescribed annual maximum of \$2,144,000.

Table 8. Overview of Use of Debt

Asset Category	Current Debt Outstanding	Use Of Debt in the Last Five Years				
		2009	2010	2011	2012	2013
Road Network	108,000	0	0	0	0	0
Bridges & Culverts	650,000	0	0	0	0	0
Storm Sewers	0	0	0	0	0	0
Total Tax Funded	758,000	0	0	0	0	0
Sanitary Sewer Network	7,994,000	0	0	5,000,000	0	0
Water Network	22,000	0	0	0	0	0
Total rate Funded	8,016,000	0	0	5,000,000	0	0
Total AMP Debt	8,774,000	0	0	5,000,000	0	0
Non AMP Debt	2,541,000	0	0	0	0	220,000
Overall Total	11,315,000	0	0	5,000,000	0	220,000

Table 9. Overview of Debt Costs

Asset Category	Principal & Interest Payments in the Next Five Years				
	2013	2014	2015	2016	2017
Road Network	32,000	31,000	29,000	28,000	0
Bridges & Culverts	63,000	63,000	63,000	63,000	63,000
Storm Sewer Network	0	0	0	0	0
Total Tax Funded	95,000	94,000	92,000	91,000	63,000
Sanitary Sewer Network	879,000	739,000	739,000	739,000	407,000
Water Network	23,000	0	0	0	0
Total Rate Funded	902,000	739,000	739,000	739,000	407,000
Total Amp Debt	997,000	833,000	831,000	830,000	802,000
Non Amp Debt	277,000	303,000	303,000	303,000	303,000
Overall Total	1,274,000	1,136,000	1,134,000	1,133,000	1,105,000

The revenue options outlined in this plan allow Prescott to fully fund its long-term infrastructure requirements without further use of debt. However, as explained in sections 7.3.2 and 7.4.2, the recommended condition rating analysis may require otherwise.

7.6 Use of reserves

7.6.1 Available reserves

Reserves play a critical role in long-term financial planning. The benefits of having reserves available for infrastructure planning include:

- the ability to stabilize tax rates when dealing with variable and sometimes uncontrollable factors
- financing one-time or short-term investments
- accumulating the funding for significant future infrastructure investments
- managing the use of debt
- normalizing infrastructure funding requirements

By infrastructure category, table 10 outlines the details of the reserves currently available to Prescott.

Table 10. Summary of Reserves Available

Asset Category	Balance at December 31, 2012
Road Network	0
Bridges	0
Storm Sewers	0
Total Tax Funded	0
Water Network	2,173,000
Sanitary Sewer Network	1,608,000
Total Rate Funded	3,781,000

There is considerable debate in the municipal sector as to the appropriate level of reserves that a municipality should have on hand. There is no clear guideline that has gained wide acceptance. Factors that municipalities should take into account when determining their capital reserve requirements include:

- breadth of services provided
- age and condition of infrastructure
- use and level of debt
- economic conditions and outlook
- internal reserve and debt policies

The reserves in table 10 are available for use by applicable asset categories during the phase-in period to full funding. This, coupled with Prescott's judicious use of debt in the past, allows the scenarios to assume that, if required, available reserves and debt capacity can be used for high priority and emergency infrastructure investments in the short to medium-term.

7.6.2 Recommendation

As Prescott updates its AMP and expands it to include other asset categories, we recommend that future planning should include determining what its long-term reserve balance requirements are and a plan to achieve such balances.

8.0 Appendix A: Report Card Calculations

Key Calculations

1. "Weighted, unadjusted star rating":

(% of assets in given condition) × (potential star rating)

2. "Adjusted star rating"

(weighted, unadjusted star rating) × (% of total replacement value)

3. "Overall Rating"

(Condition vs. Performance star rating) + (Funding vs. Need star rating)

2

Grade Cutoffs

1. Conditions vs Performance

Letter Grade	Star Rating
F	0
D	2
D+	2.5
C	2.9
C+	3.5
B	3.9
B+	4.5
A	4.9
A	5

2. Funding vs Need

Funding %	Star rating	Grade
0.0%	0	F
25.0%	1	F
46.0%	1.9	D
61.0%	2.9	C
76.0%	3.9	B
91.0%	4.9	A
100.0%	5	A

1. Condition vs. Performance

Total category replacement value \$19,785,224		Segment replacement value \$19,785,224		Segment value as a % of total category replacement value			
Segment	Condition	Letter grade	Star rating	Quantity (m.sq) in given condition	% of Assets in given condition	Weighted, unadjusted star rating	Segment adjusted star rating
Roads and sidewalks (excludes gravel)	Excellent	A	5	164,869	53%	2.67	4.1
	Good	B	4	80,642	26%	1.05	
	Fair	C	3	24,711	8%	0.24	
	Poor	D	2	2,346	1%	0.02	
	Critical	F	1	35,918	12%	0.12	
Totals				308,486	100%	4.09	

Category star rating	4.1	Category letter grade	B
----------------------	-----	-----------------------	----------

2. Funding vs. Need

Average annual investment required	2013 funding available	Funding percentage	Deficit	Category star rating	Category letter grade
\$685,000	\$339,000	49.5%	\$346,000	1.9	D

3. Overall Rating

Condition vs Performance star rating	4.1	Funding vs. Need star rating	1.9	Average star rating	3.0	Overall letter grade	C
--------------------------------------	-----	------------------------------	-----	---------------------	-----	----------------------	----------

1. Condition vs. Performance

Total category replacement value		\$5,463,634		Segment replacement value		\$5,463,634		Segment value as a % of total category replacement value		100.0%	
Segment	Condition	Letter grade	Star rating	Quantity (m.sq) in given condition	% of Assets in given condition	Weighted, unadjusted star rating	Segment adjusted star rating				
Bridges	Excellent	A	5	0	0%	0.00	4.0				
	Good	B	4	940	100%	4.00					
	Fair	C	3	0	0%	0.00					
	Poor	D	2	0	0%	0.00					
	Critical	F	1	0	0%	0.00					
Totals				940	100%	4.00					

Category star rating	4.0	Category letter grade	B
----------------------	-----	-----------------------	----------

2. Funding vs. Need

Average annual investment required	2013 funding available	Funding percentage	Deficit	Category star rating	Category letter grade
\$188,000	\$1,000	0.5%	\$187,000	0.0	F

3. Overall Rating

Condition vs Performance star rating	4.0	Funding vs. Need star rating	0.0	Average star rating	2.0	Overall letter grade	D
--------------------------------------	-----	------------------------------	-----	---------------------	-----	----------------------	----------

1. Condition vs. Performance

Segment	Condition	Letter grade	Star rating	Quantity (m) in given condition	Segment replacement value	% of Assets in given condition	Weighted, unadjusted star rating	Segment value as a % of total category replacement value
Total category replacement value \$90,585,654								
Mains	Excellent	A	5	3,456		11%	0.55	26.9%
	Good	B	4	4,021		13%	0.52	
	Fair	C	3	2,489		8%	0.24	
	Poor	D	2	504		2%	0.03	
	Critical	F	1	20,750		66%	0.66	
	Totals				31,220		100%	
Total category replacement value \$90,585,654								
Segment	Condition	Letter grade	Star rating	Units in given condition	Segment replacement value	% of Assets in given condition	Weighted, unadjusted star rating	Segment value as a % of total category replacement value
Total category replacement value \$7,735,091								
Appurtenances	Excellent	A	5	661		29%	1.43	25.3%
	Good	B	4	421		18%	0.73	
	Fair	C	3	331		14%	0.43	
	Poor	D	2	592		26%	0.51	
	Critical	F	1	314		14%	0.14	
	Totals				2,319		100%	

Segment	Condition	Letter grade	Star rating	Quantities (\$) given condition	Segment replacement value	% of Assets in given condition	Weighted, unadjusted star rating	Segment value as a % of total category replacement value
Total category replacement value \$14,619,164								
Facilities	Excellent	A	5	\$573,049		4%	0.20	47.8%
	Good	B	4	\$9,619,421		66%	2.65	
	Fair	C	3	\$4,366,695		30%	0.90	
	Poor	D	2	\$0		0%	0.00	
	Critical	F	1	\$0		0%	0.00	
	Totals				\$14,619,165		100%	

2. Funding vs. Need		Category star rating	Category letter grade
Average annual investment required	\$421,000	3.1	C
2013 funding available	\$241,000		
Funding percentage	57.2%		
Deficit	\$180,000		
Funding vs. Need star rating	1.9	1.9	D

3. Overall Rating		Overall letter grade	
Condition vs Performance star rating	3.1	Average star rating	2.5
Funding vs. Need star rating	1.9		
			D+

1. Condition vs. Performance

Total category replacement value \$39,216,624		Segment replacement value \$10,932,543		Segment value as a % of total category replacement value 27.9%			
Segment	Condition	Letter grade	Star rating	Quantity (m) in given condition	% of Assets in given condition	Weighted, unadjusted star rating	Segment adjusted star rating
Mains	Excellent	A	5	8,315	27%	1.35	0.9
	Good	B	4	5,148	17%	0.67	
	Fair	C	3	9,575	31%	0.93	
	Poor	D	2	5,734	19%	0.37	
	Critical	F	1	1,987	6%	0.06	
Totals				30,759	100%	3.39	

Total category replacement value \$39,216,624		Segment replacement value \$28,284,081		Segment value as a % of total category replacement value 72.1%			
Segment	Condition	Letter grade	Star rating	Quantities (\$) given condition	% of Assets in given condition	Weighted, unadjusted star rating	Segment adjusted star rating
Facilities	Excellent	A	5	\$21,164,001	75%	3.74	2.9
	Good	B	4	\$0	0%	0.00	
	Fair	C	3	\$0	0%	0.00	
	Poor	D	2	\$0	0%	0.00	
	Critical	F	1	\$7,120,080	25%	0.25	
Totals				\$28,284,081	100%	3.99	

Average annual investment required \$716,000		2013 funding available \$146,000		Funding percentage 20.4%		Category star rating 3.8		Category letter grade C+	
--	--	----------------------------------	--	--------------------------	--	--------------------------	--	---------------------------------	--

2. Funding vs. Need

Average annual investment required \$716,000		2013 funding available \$146,000		Funding percentage 20.4%		Category star rating 3.8		Category letter grade C+	
Condition vs Performance star rating 3.8		Funding vs. Need star rating 0.0		Average star rating 1.9		Category star rating 0.0		Category letter grade F	

3. Overall Rating

Condition vs Performance star rating 3.8		Funding vs. Need star rating 0.0		Average star rating 1.9		Overall letter grade D	
--	--	----------------------------------	--	-------------------------	--	-------------------------------	--

1. Condition vs. Performance

Total category replacement value \$12,295,543		Segment replacement value \$8,404,578		Segment value as a % of total category replacement value 68.4%			
Segment	Condition	Letter grade	Star rating	Quantity (m) in given condition	% of Assets in given condition	Weighted, unadjusted star rating	Segment adjusted star rating
Mains	Excellent	A	5	5,295	30%	1.50	2.5
	Good	B	4	5,113	29%	1.15	
	Fair	C	3	4,363	25%	0.74	
	Poor	D	2	2,937	17%	0.33	
	Critical	F	1	0	0%	0.00	
Totals			17,708	100%	3.72		

Total category replacement value \$12,295,543		Segment replacement value \$3,888,765		Segment value as a % of total category replacement value 31.6%			
Segment	Condition	Letter grade	Star rating	Units in given condition	% of Assets in given condition	Weighted, unadjusted star rating	Segment adjusted star rating
Appurtenances	Excellent	A	5	207	28%	1.40	1.2
	Good	B	4	245	33%	1.33	
	Fair	C	3	206	28%	0.84	
	Poor	D	2	79	11%	0.21	
	Critical	F	1	2	0%	0.00	
Totals			739	100%	3.78		

Category star rating		Category letter grade
3.7		C+

2. Funding vs. Need


Average annual investment required	2013 funding available	Funding percentage	Deficit	Category star rating	Category letter grade
\$154,000	\$70,000	45.5%	\$84,000	1.0	F

3. Overall Rating


Condition vs Performance star rating	Funding vs. Need star rating	Average star rating	Overall letter grade
3.7	1.0	2.4	D

Infrastructure Replacement Cost Per Household

Total: \$51,607 per household



Daily Investment Required Per Household for Infrastructure Sustainability



**CUPE EMPLOYEES OVERTIME HOURS
AS OF P.P. # 18 ENDING AUGUST 30, 2014**

	OT @ 1.5 HOURS	OT @ 2.0 HOURS	TOTAL OVERTIME HOURS
Steve Summers	20.0	17.0	37.0
Ed Yandeu	312.5	102.5	415.0
Gary Minkhorst	81.0	65.5	146.5
Bob Dixon	53.0	12.5	65.5
Bill Shanahan	128.5	65.5	194.0
Phil Burton	75.5	13.0	88.5
Andrew Wilson	50.0	5.0	55.0
Matt McCaw	90.0	33.0	123.0
Carl Groulx	51.5	37.5	89.0
Randy Hopkins	20.0	6.0	26.0
TOTAL	882.0	357.5	1239.5
<p>Note: This chart reflects overtime hours paid. It does not include any accrued/earned overtime hours that are unpaid.</p>			